

## Product profile

# PB42

## Portable Printer



- Intermec Designed & Manufactured
- Dual high capacity Lithium Ion batteries
- Intermec SmartSystems™ Device Management
- Serial, USB and Bluetooth® Class 1 Interfaces
- Frontloading batteries
- Flexibility to use roll or fanfold receipt paper
- High visibility buttons and indicators
- International logos facilitate global use
- Simple paper installation
- Operates in temperatures as low as -20° C

Intermec's PB42\* four inch wireless portable receipt printer is designed to improve direct store delivery (DSD), Field Service, and Home Utility applications. The PB42 printer interfaces seamlessly with the CK60 and 700 Intermec handheld computers. Daily route activities are easily entered and tracked via a mobile computer throughout a workers shift. Receipts are immediately provided to the customer for prompt payment or to eliminate duplicate billing efforts.

The unique Intermec design of the PB42 portable receipt printer ensures ease of use. This is very important for delivery drivers who negotiate routes with multiple stops and rugged conditions. Special design features include sharing of battery design with the CK60 mobile computer, simple receipt paper installation, high visibility buttons and indicators to show when the printer is within radio range or when the lithium ion batteries are getting low.

Charge up to four printers at once with the unique four bay charger. Printers "drop-in" and charge from hinge pins; no charge cable required. Frontloading batteries that can be removed with just one hand. Lexan® media windows conveniently show media status. Standard belt clip & hand strap also add to the convenience of operation.

The Intermec Ready-to-Work Indicator is integrated into the PB42 printer. This is part of the Intermec SmartSystems™ and provides a visual cue to the operating state of the printer.

Intermec's PB42 portable receipt printer is ideal for use worldwide. The PB42 printer features widely recognized international logo indicators on the buttons, multiple language character sets, and worldwide certifications. The PB42 printer is ideal for streamlining processes and route deliveries in DSD, field service, and home utility industries worldwide.



\*All references to the Intermec PB42 Portable Printer apply equally to the PB42c model.

## Application

Thermal receipt printing

## Physical Characteristics

**Depth:** 3.1 inches (7.87 cm)

**Height:** 7.1 inches (18.03 cm)

**Width:** 6.62 inches (16.82 cm)

**Weight:** 3.0 lb (1.36 kg) w/ 2 battery packs and full roll receipt paper

**Drop test:** 4 ft to concrete

## Print Specifications

**Print Width:** 4.1 inch (104 mm)

**Element Size:** 0.0049 inch (0.125mm)

**Minimum Graphical Element:** 0.010 inch (0.254 mm)

## Print Speed

2 ips (50 mm/sec)

## Print Resolution

203 DPI (8 dots/mm)

## Receipts

**Max. Width:** 4.4 inch (111.8 mm)

**Thickness:** 0.002 to .0044 inch (0.05 to 0.112 mm)

**Tracking:** Center

**Style:** Roll-fed or fanfold

**Roll Max Diameter:** 2.65 inches (67 mm)

**Roll Core ID:** 0.75 inch (19.05 mm)

**Media Type:** Receipt paper

## Standard Interface

Serial RS-232 (115 kbps)

USB v.1.1 (full speed)

Class 1 Bluetooth®

## Optional Interface

Class 1 Bluetooth® - range up to 100 m (328 feet)

## Character Sets

**West European Latin No. 1 and**

**9:** Danish, Dutch, English, Faeroese, Finnish, French, German, Icelandic, Irish, Italian, Norwegian, Portuguese, Spanish, and Swedish.

**East European Latin No. 2:**

Albanian, Czech, English, German, Hungarian, Polish, Rumanian, Serbocroatian, Slovak, and Slovene.

**Cyrillic:** Bulgarian, Byelorussian, English, Macedonian, Russian, Serbocroatian, and Ukrainian.

**Arabic**

**Greek**

**Hebrew**

**U.S. standard**

**Europe multilingual**

**Code Page requirements for Far East**

Log onto [www.intermec.com](http://www.intermec.com) for additional international fonts for the PB42 portable printer.

## Font types

40 column, normal, bold, 80 column, normal, bold, 132 column, normal, bold

## Standard Memory

16 MB SDRAM

4 MB Flash

## LED Indicators

Intermec Ready-to-Work Indicator

Radio - Green Flashing

Battery - Green/Red

## Power Supply

**AC Adapter:** 50 Watt

**Voltage Range:** 12 V  $\pm$  5%.

**Rechargeable Li-Ion Battery:** 7.2V, 2.4A-H. Each printer ships standard with two batteries (batteries do not ship with vehicle mount option).

## Operating Environment

**Operating:** -20°C (-4°F) to 50°C (122°F)

**Non-operating:** -30°C (-22°F) to 70°C (158°F)

**Battery Charging:** 0°C (32°F) to 50°C (122°F)

**Relative Humidity:** 10% to 90% non-condensing

## Regulatory Approvals

North America UL and cUL Listed, UL 60950; Europe TÜV Rheinland GS Licensed, EN 60950; Mexico NYCE CERTIFIED, NOM 19; Other Countries EN 60950 CB; CE Mark

## EMC Approvals

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN 55022 Class B + EN 55024); CISPR22

## Options & Accessories

Belt Clip, Shoulder Strap, Batteries, AC Charger, Vehicle Mount, External Paper Tray, AC Power Adapter, Cigarette Lighter Adapter, Nylon System Case, Four Bay Printer Charger

## North America

### Corporate Headquarters

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

### South America & Mexico Headquarters Office

Rua Samuel Morse,  
120-9º. Andar  
Brooklin - 04576-060  
São Paulo/SP - BRAZIL  
Phone: +55 11 5502.6770  
Fax: +55 11 5502.6780  
[www.intermec.com.br](http://www.intermec.com.br)

## Europe/Middle East &

### Africa Headquarters Office

Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

## Asia Pacific

Headquarters Office  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

## Internet

[www.intermec.com](http://www.intermec.com)  
Worldwide Locations:  
[www.intermec.com/locations](http://www.intermec.com/locations)

## Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW: 00 800 4488 8844  
Toll ROW: +44 134 435 0296

## OEM Sales

Phone: (425) 348-2762

## Media Sales

Phone: (513) 874-5882

## Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

Copyright © 2009 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611578-01L 02/09

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

