stor FVP-10



- Front Loading
- Under-The-Counter Mountable
- Platform Top Cover Increases Counter Space
- Drip Proof (IPX1 Certified)
- Voice Enabled Communication Tool
- Ultra High Speed Receipt Printing (250mm/sec)



Helps Protect from Liquids & Dust



For Limited Counter Space

The Under the Counter Under the Counter Conne Output The Under the Counter Conne The Under the Counter Counter Conne The Under the Counter Counter

Space Enabling Design



User Communication Tool



















Front Loading, Voice Enabled Platform Printer

The FVP-10 is designed to bring an array of new benefits like front loading, onboard USB, receipt compression for paper saving and multiple mounting options due to its "platform" design combined with the high quality and high-speed printer performance that POS users have come to expect from Star.

Star Micronics has developed the FVP-10 to assist users who:

- Have counter space challenges
- Require a splash and dust resistant printer
- Need to print a receipt as fast as possible to decrease customer wait time
- Want to communicate to staff and customers in a language they understand

The FVP-10 features an ultra high print speed of 250mm/sec and front paper loading for easy paper roll changing. Its square design & front paper loading allow for it to be easily under-counter mounted or used as a platform to mount other devices. The FVP-10 can support up to 7 pounds of accessories on its top. Text to voice feature enables users to communicate important information with both staff and customers. For example Voice alerts to remind an operator to start a specific task can easily be programmed to be spoken before or after the print job.

3 Models Available:

- •Standard FVP-10USB with CD and USB cable but **no** power supply
- The Platform FVP-10USB with CD, USB Cable, Platform Extension and Power supply
- •The Under the Counter FVP-10USB with CD, USB Cable, Under the Counter Connecting Kit and Power Supply

FVP-10 Specifications

	Front Loading, Voice Enabled Platform Printer	
Features	Hardware Front Paper Exit Voice Enabled Platform Top Housing Increases Available Counter Space Ultra Fast (250mm/s) Standard USB Connection with Extra Swappable Interface Splash Resistant Under-the-Counter Mountable "Drop-In & Print" Paper Loading Label Printing Support Reliable Guillotine Cutter Durable Enclosure Design Small Footprint Two Color Print Capable Recessed Cable Connections ESC/POS™ Emulation Supported	Software Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Configuration Setup Utility Ethernet Interface Setup Utility Virtual Serial Port for Legacy Applications Audio Feedback Triggered by User-Defined Text Keys StarlO SDK
Note: Connections in bold are supported; grayed-out connection types may be supported by special request.	9-Pin Serial 25-Pin Serial Parallel USB Powered USB Ethernet WiFi Dual 9-Pin Serial/USB	Virtual Serial Port to USB Virtual Serial Port to Ethernet Virtual TCP/IP Port
Drivers	Windows® XP Vista (32 bit / 64 bit) Windows 7 (32 bit / 64 bit) Server 2008 (32 bit / 64 bit) CE XP Embedded POS for .NET	OPOS™ JavaPOS™ USB Vendor Class Linux™ CUPS Mac OS X CUPS
What's Included	FVP-10 Cutter Printer (Gray Case Only) Installation CD (Printer Driver / Utility / Manuals) 1.8m USB Cable Interface Cover Power Switch Cover Setup Sheets Start Up Paper Roll	Model FVP-10U (Printer, USB Cable) Model FVP-10U Platform (Printer, USB Cable, Power Supply, 3.5" Extension for Platform Use) Model FVP-10U Under the Counter (Printer, USB Cable, Power Supply, Under Counter Mounting Kit)
Optional Accessories	3.5" Extension for Platform Use Under Counter Mount Kit Power Supply (PS60A)	Parallel Interface Board Serial Interface Board Ethernet Interface Board PoweredUSB Interface Board
Technical Specifications	Print Method: Direct Thermal Print Speed: 250mm/s (54 Receipts Per Minute) Paper Width: 58 – 80mm (Adjustable) Paper Thickness: 0.06 – 0.15mm Paper Diameter: Max 83mm Emulation: Star Line Mode, ESC/POS™	Power: DC24V Resolution: 203 dpi MCBF: 60 Million Lines Cutter: 2 Million Cuts Dimensions: W=144mm, H=114mm, D=227.7mm
Warranty	For US and Canada: 3-Year Limited Warranty, Plus Optional Extended Services Agreement Policies (Extend-A-Star and Swap-A-Star)	
For Further Information	Sales: 1-800-782-7636 x107 Technical Support: 1-800-782-7636 x105	Web: http://www.starmicronics.com





www.L-TronDirect.com 800-830-9523 info@L-Tron.com

