

# ACP-4320

## Quiet 4U Rackmount Chassis with Dual Hot-Swap SAS/SATA HDD Trays



### Features

- Supports either an ATX motherboard or a PICMG backplane with up to 15 slots
- Support dual SAS/SATA hot-swap HDD trays
- LED indicators and alarm notification for system fault detection
- Low noise system fans
- Built-in Intelligent System Module enabling whole system fan control and remote manageability


Quiet

CE FCC RoHS

### Specifications

Driver Bay	5.25"	External	Internal
	3.5"	2	-
	Hot Swap	1 SAS/SATA Tray	-
Cooling	Fan	2 (compatible with 3.5" or 2.5" devices)	
	Air Filter	1(12 cm/74 CFM) + 1 (6cm / 28 CFM)	
	Smart Fan	Yes	
Front I/O Interface	USB 2.0	System fan speed referring to chassis thermal sensor, or CPU temperature (Available with selected Advantech MBs/CPU cards)	
	LED Indicators	2	
Miscellaneous	Power, HDD, temperature, fan, LAN1 and LAN2	Backplane version: One 9-pin D-Sub opening	
	Rear Panel	Motherboard version: Five 9-pin D-Sub opening and one 68-pin SCSI opening	
Intelligent System Module Remote Monitoring	CPU/System fan speed , CPU/System temperature , motherboard voltage (Only selected Advantech MBs/CPU cards with SUSIAccess installed can fully enable these functions, check with Advantech local rep. for detailed information.)		
Environment	Temperature	Operating	Non-Operating
	Humidity	0 ~ 40° C (32 ~ 104° F)	- 20 ~ 60° C (-4 ~ 140° F)
	Vibration (5 ~ 500 Hz)	10 ~ 85% @ 40° C , non-condensing	10 ~ 95% @ 40° C, non-condensing
	Shock	1 Grms	2 G
Physical Characteristics	Dimension (W x H x D)	10G ( with 11 ms duration, half sine wave )	30 G
	Weight	482 x 177 x 479 mm (19" x 7.0" x 18.9")	17.6 kg (38.7lb)

### Front View




### Inside View

Easy-to-maintain system fan



## Dimensions

Unit: mm [inch]



## Ordering Information

Model Name	Description
ACP-4320BP-00BE	Full-sized PICMG 1.0/1.3 BP version, without PSU
ACP-4320MB-00BE	MB version, without PSU
ACP-4320BP-40BE	Full-sized PICMG 1.0/1.3 BP version, with 400W PSU
ACP-4320MB-40BE	MB version, with 400W PSU

## Optional Accessories

Part Number	Description
IDT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays
IDT-5230E	Mobile rack for converting dual 5.25" drive bays to three 3.5" SAS/SATA HDD trays

## Power Supply Options

Part Number	80 Plus Grade	Wattage	Type	Input
PS8-300ATX-ZBE	Bronze	300W	Single	AC 100 ~ 240 V (full range)
PS8-400ATX-ZE	Bronze	400W	Single	AC 100 ~ 240 V (full range)
PS8-500ATX-ZE	Bronze	500W	Single	AC 100 ~ 240 V (full range)
RPS8-350ATX-XE	Gold	350W	1+1 Redundant	AC 100 ~ 240 V (full range)
RPS8-500ATX-XE	Bronze	500W	1+1 Redundant	AC 100 ~ 240 V (full range)

## Spare Parts

Part Number	Description
1990001299	Fan filter 95 x 130 mm
1990001298	Door filter 150 x 68 mm



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

