

# ADAM-2051Z

# ADAM-2051PZ

## Wireless Sensor Network 8-ch Digital Input Node

## Wireless Sensor Network 8-ch Digital Input Node with Power Amplifier



ADAM-2051Z



### Features

- IEEE 802.15.4 Wireless Standard
- Supports Star/Tree/Mesh Network Topologies
- Modbus Communication Protocol
- Low Power Consumption
- LED Indicators
- Event Triggering

### Specifications

#### Digital Input

- Channels** 8
  - Input Resistance** 10 K $\Omega$
  - Input Level**
    - Dry contact: Logic level 0: Close to GND  
Logic level 1: Open
    - Wet contact: Logic level 0: 0-0.8 V max  
Logic level 1: 2.0 ~ 5.0 V
- (Note: The Digital Input Level 0 and 1 status can be inverted)

### Ordering Information

- ADAM-2051Z\*** Wireless 8-ch Digital Input Node



ADAM-2051PZ



### Features

- IEEE 802.15.4 Wireless Standard
- Supports Star/Tree/Mesh Network Topologies
- Modbus Communication Protocol
- LED Indicators
- Event Triggering

### Specifications

#### Digital Input

- Channels** 8
  - Input Resistance** 10 K $\Omega$
  - Input Level**
    - Dry contact: Logic level 0: Close to GND  
Logic level 1: Open
    - Wet contact: Logic level 0: 0-0.8 V max  
Logic level 1: 2.0 ~ 5.0 V
- (Note: The Digital Input Level 0 and 1 status can be inverted)

### Ordering Information

- ADAM-2051PZ\*** Wireless 8-ch Digital Input Node with Power Amplifier

## Common Specifications

### Wireless Communication

- IEEE Standard** IEEE 802.15.4
- Modulation Type** DSSS (OQPSK)
- Frequency Band** ISM 2.4 GHz  
(2.4 GHz ~ 2.4835 GHz)
- Channels** 11 - 26
- RF Data Rate** 250 Kbps
- Transmit Power Typ.** 3  $\pm$  1 dBm (ADAM-2051Z)  
19  $\pm$  1 dBm (ADAM-2051PZ)
- Receiver Sensitivity** -97 dBm
- Topologies** Star / Tree / Mesh
- Outdoor Range** 110 m with line of sight (ADAM-2051Z)  
1000 m with line of sight (ADAM-2051PZ)
- Function** End Device

### General

- Connectors** 1 x plug-in terminal block (#14 ~ 22 AWG)
- Power Input** Unregulated 10 ~ 30 V<sub>DC</sub>
- Battery Input** 2 x AA Alkaline
- Power Consumption** 0.3 W @ 24 V<sub>DC</sub>  
(ADAM-2051Z/PZ) Battery AA \* 2  
380 uW @ 3 V<sub>DC</sub> (1 minute Tx Interval)  
220 uW @ 3 V<sub>DC</sub> (2 minute Tx Interval)  
130 uW @ 3 V<sub>DC</sub> (5 minute Tx Interval)

### Environment

- Operating Temperature**
  - External Power -20°C ~ 70°C (-4°F ~ 157.9°F)
  - Battery Power 0°C ~ 50°C (32°F ~ 122°F)
- Storage Temperature** -20°C ~ 70°C (-4°F ~ 157.9°F)
- Operating Humidity** 20-95% RH
- Storage Humidity** 0-95% RH

\*If want to operate in a wider temperature (-40°C~ 85°C (-4°F ~ 157.9°F) ), contact our sales team.



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

