

FPM-7211W

21.5" Full HD Industrial Monitor with PCT Touch, Direct-VGA and DVI Ports

NEW



Features

- 21.5" Full HD TFT LED LCD wide screen display
- 16:9 wide screen display, view area increases by 40%
- Supports 10 points multi-touch via USB interface in Windows 7/8
- Slim type design for Panel mount / Wall mount easy installation
- Various mounting options: panel, wall, desktop and VESA arm mounting
- Projected Capacitive Touchscreen with reliable glass surface
- Robust design with SECC chassis and Magnesium alloy front panel with IP66 compliance
- OSD control pad on rear cover
- Lockable I/O connectors

Introduction

With its brand new design, the FPM-7211W provides a new wide screen display size with industrial grade design concept. By truly-flat touch screen, the front bezel meets IP66 testing criteria. FPM-7211W projected capacitive touch can support 10-points touch application. New easy installation design can help you with one person for panel mounting. FPM-7211W monitor with slim enclosure is ideally suited to being either panel or wall mounted.

Specifications

General

- OSD Controls** OSD control in rear cover
- Certification** BSMI, CCC, CE, FCC Class A, UL
- Dimensions (W x H x D)** 558.4 x 349.8 x 47.7 mm (21.98" x 13.77" x 1.88")
- Enclosure** Front panel: Die-cast Magnesium alloy
Rear cover: SECC
- Mounting** Panel, wall, desktop, VESA (MIS,100,C)
- Power Input** Phoenix x Jack: 24 V_{DC} input
DC Jack: external 57 W power adapter, with 100 ~ 240 V_{AC} input and 12 V_{DC} @ 4.75 A output

Note: AC power adapter is included.

- Power Consumption** 25 W + 20%
- Video Port** VGA & DVI-D port
- Weight (Net)** 8kg (17.6lbs)

LCD Display

- Display Type** Full HD TFT LED LCD
- Display Size** 21.5"
- Max. Resolution** 1920 x 1080
- Max. Color** 16.7 M
- Viewing Angle (H/V°)** 178/178
- Luminance (cd/m²)** 300
- Backlight Life (hrs)** 50,000
- Contrast Ratio** 5000:1

Touchscreen

- Type** Projected Capacitive touch
- Interface** RS-232 and USB
- Light Transmission** Above 75%
- OS Support** Windows XP, Vista, 7, 8, XPe and Linux
- Multi Touch** 10 points, USB interface in Win 7/8.
- Hardness** >6H

Environment

- Operation Temperature** 0 ~ 55°C (32 ~ 131°F)
- Storage Temperature** -20 ~ 60°C (-4 ~ 140°F)
- Humidity (Storage)** 10 ~ 90% non-condensing
- Waterproof** Front panel is IP66 compliant
- Vibration** 5 ~ 500 Hz, 1 Grms (Operating, Random)

Ordering Information


- FPM-7211W-P3AE** 21.5" Full HD Ind Monitor w/PCT TS (RS-232, USB)

Accessories

- 1702002600** Power Cable US Plug 1.8 M
- 1702002605** Power Cable EU Plug 1.8 M
- 1702031801** Power Cable UK Plug 1.8 M
- 1700000596** Power Cable China/Australia Plug 1.8 M
- FPM-7181W-SMKE** FPM-7211W Mounting kit for desktop & wall

Dimensions


Unit: mm [inch]



Panel Cut-out Dimensions: 550.30 x 341.8 mm (21.67" x 13.46")


Easy Installation

Snap hook in rear cover




Screw to set up the snap hook out of upper side

Stopper Screw in rear cover



Screw for the stopper screw out of down side

Rear View





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

