
# **PCI-1757UP**

## 24-ch Digital I/O Low Profile Universal **PCI Card**



#### **Features**

- Low profile PCI form factor
- Universal PCI bus
- 24 TTL level digital I/O channels
- Emulates mode 0 of 8255 PPI
- Buffered circuits provide higher driving capability
- Interrupt handling capability
- Output status read-back
- I/O configurable by software or on board DIP switch
- Keeps the output settings and values after system hot reset
- BoardID™ switch
- Convenient DB25 connector
- · Supports both dry and wet contact

# FCC ( E COMPLIANT STORY STORY

### Introduction

PCI-1757UP is a 24-channel digital I/O low profile PCI card that meets the PCI standard REV.2.2 (universal PCI expansion card). The card also works with 3.3 V and 5 V PCI slots, and provides you with 24 parallel digital input/output channels that emulate mode 0 of the 8255 PPI chip. However, the buffered circuits offer a higher driving capability than the 8255.

## **Specifications**

#### **Digital Input**

24 (shared with output) Channels

5 V/TTL Compatibility

 Input Voltage Logic 0: 0.8 V @ -0.2 mA Logic 1: 2.0 V @ 20 mA

• Interrupt Capable Ch.

#### **Digital Output**

Channels 24 (shared with input)

 Compatibility 5 V/TTL

 Output Voltage Logic 0: 0.5 V max.

Logic 1: 3.7 V min.

 Output Capability Sink: 0.5 V @ 24 mA

Source: 3.7 V @ 24 mA

#### General

Bus Type Universal PCI V2.2 I/O Connectors 1 x DB25 female connector

 Dimensions (L x H) 120 x 64 mm (4.7" x 2.5") Low profile MD1

Typical: 5 V @ 140 mA Power Consumption

Max.: 5 V @ 200 mA

• Operating Temperature  $0 \sim 70^{\circ}\text{C} (32 \sim 158^{\circ}\text{F})$ Storage Temperature

-20 ~ 80°C(-4 ~ 176°F) Storage Humidity 5 ~ 95% non-condensing

## **Ordering Information**


■ PCI-1757UP 24-ch Digital I/O Low Profile Universal PCI Card

#### **Accessories**

DB25 DIN-rail Wiring Board ADAM-3925

PCL-10125-1E DB25 Cable, 1 m PCL-10125-3E DB25 Cable, 3 m

# **Pin Assignments**





www.L-TronDirect.com 800-830-9523 info@L-Tron.com

