

## ORDERING INFORMATION

Mini	Description	P/N	Track(s)	Color	Full-Size	Description	P/N	Track(s)	Color
Mini	USB Keyboard Emulation	21040109	1 & 2	White	Full-Size	USB Keyboard Emulation	21088066	1, 2 & 3	White
		21040107	1, 2 & 3	White			Port Powered RS-232	21088061	1, 2 & 3
	USB HID	21040105	2	White		Keyboard Wedge		21080057	1 & 2 mini DIN
		21040106	2	Black			21080141	1 & 2 mini DIN	Black
		21040103	1 & 2	White			21080020	1 & 2 large DIN	White
21040104		1 & 2	Black						
21040101		1, 2 & 3	White						
Port Powered RS-232	21040102	1, 2 & 3	Black						
	21040075	2	White						
	21040080	2	Black						
	21040071	1 & 2	White						
	21040079	1 & 2	Black						
	21040073	2 & 3	White						
	21040074	1, 2 & 3	White						
Keyboard Wedge	21040082	1, 2 & 3	Black						
	21080205	2	White						
	21080206	2	Black						
	21080203	1 & 2	White						
	21080204	1 & 2	Black						
	21080201	1, 2 & 3	White						
	21080202	1, 2 & 3	Black						

## SPECIFICATIONS

Mini & Full-Size	Reference Standards	ISO, ANSI, CDL and AAMVA	Mini	USB	Current	
Mini & Full-Size	Recording Method	Two-frequency coherent phase (F2F)	Mini & Full-Size	Keyboard Wedge	Normal: 30 mA	
	Card Speed	3 - 50 i.p.s.			Suspend Mode: 300 uA	
	MTBF	Electronics: 125,000 hours Head: 1,000,000 passes		Port Powered RS-232	Current	Quiescent: 1 - 2 mA typical (continuous)
Audible Noise	55db at 39.4 in (1.0 m)	Transmitting: 8 - 9 typical (5 ms duration)				
Mini & Full-Size	Temperature	Operating: 32°F - 131°F (0°C - 55°C) Storage: -22°F - 158°F (-30°C - 70°C)	Full-Size	Keyboard Wedge	Peak at Power On: 12 mA	
	Humidity	Operating: 10% - 90% non condensing Storage: 0% - 100% non condensing			DTR Voltage	5 - 15 VDC
Mini & Full-Size	Altitude	Operating: 0 - 10,000 ft (0 - 3,048 m) Storage: 0 - 50,000 ft (1 - 15,240 m)	Full-Size	Keyboard Wedge	Current	100 mA max
					Power Input	From PC: 5 V, 100 mA max draw

### MagTek® Inc.


1710 Apollo Court  
Seal Beach, CA 90740  
p 562-546-6400  
f 562-546-6301

www.magtek.com  
800-788-6835

REGISTERED TO ISO 9001:2000

**MAGTEK®**

## COMPLETE CARD READING SOLUTIONS



magtek.com


Mini & Full-Size Swipe Readers

MagTek, the world's leading supplier of magnetic stripe card readers since 1972, offers quality swipe readers designed to help process your business's card transactions easily, effectively and securely.

The Mini Swipe Reader and the Full-Size Swipe Reader, two of our most popular card reading solutions, have been designed to meet a variety of installation needs and functional requirements.

Our Mini Swipe Reader's small foot print saves space while our Full-Size Reader offers the longer card path that ensures easy, accurate swiping every time.

Designed to work with most software applications and PCs, MagTek's Mini and Full-Size Swipe Readers allow for several possible interface configurations to handle the transfer of card data into your system.




### Mini Swipe Reader

Space-saving design



### Full-Size Swipe Reader

Longer card path for easy swipe



#### Features\*

- ▶ No external power source required
- ▶ Reads up to three tracks of data
- ▶ Compatible with most computers and terminals
- ▶ Reads encoded cards that meet ISO/ANSI/AAMVA standards
- ▶ Green/red LED status
- ▶ Bidirectional read capability
- ▶ Up to 1,000,000 passes with ISO conforming cards
- ▶ Available in black or white

\* Features apply to both Mini & Full-Size Swipe Readers

#### USB Keyboard Emulation

- ▶ Ideal for existing keyboard wedge applications
- ▶ No software interface required to view card data
- ▶ Raw data transferred to PC and display on screen as if keyed in manually
- ▶ Built-in 6-foot cable with standard USB connector

#### USB (HID)

[Available for Mini Swipe Reader only]

- ▶ Ideal for new card reading applications
- ▶ Application software required to display data [demo software available]
- ▶ Plugs into PC with minimal setup
- ▶ Uses standard window HID driver for communications. No third party device drivers required
- ▶ Compliant with Human Interface Device (HID) standards
- ▶ Built-in 6-foot cable with standard USB connector

#### RS-232 (Serial Interface)

- ▶ Ideal for applications needing full communication to and from device
- ▶ Software interface required to view card data
- ▶ Interfaces with existing serial applications
- ▶ Standard ASCII message format offers maximum flexibility for application integration
- ▶ 9-pin serial connector

#### Keyboard Wedge

- ▶ Ideal for use with PCs that have no available serial port
- ▶ No software interface required to view card data
- ▶ Transfer of card data via a link between keyboard port and keyboard
- ▶ Raw data transferred to your computer and displayed on screen as if keyed in manually
- ▶ Available with traditional 6 pin or 5 pin DIN connector



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

