



DT-2000-TB

KEYBOARD WITH INTEGRATED TRACKBALL

The DT-2000-TB is constructed using a highly-rugged stainless steel case and industrial silicone rubber pad, ensuring NEMA 4X protection. The DT-2000-TB's trackball pointing device is a completely sealed 38-mm laser unit, featuring a removable ball for convenient cleaning, as well as an adjustable tension ring. The trackball is operated using sealed stainless steel switches with left and right click functions and a third programmable button.

- Features:
- 10-Key Numeric Pad
 - 114-Key Functionality
 - 24 Function Keys
 - Integrated Trackball
 - PS/2 and Separate-Cable USB configurations available

Product Code DT-2000-TB

SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3.04 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or two USB cables
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in (1.4 mm) ACTUATION FORCE: 7.03 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 50mA@5V (from Keyboard port) POINTER: 45mA@5V (from Mouse port) USB: 95mA@5V (from CPU port)
Compatability	PS/2 KEYBOARD/TRACKBALL: All Windows Operating Systems USB KEYBOARD/TRACKBALL: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to 85C (-40F to 185F) OPERATING: 0C to 70C (32F to 158F)
WEIGHT	8.25 lbs+/- 0.10 lbs (3.74 kg 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

