



## DT-5K-NI

### STAINLESS STEEL NONINCENDIVE KEYBOARD

iKey offers a full line of nonincendive keyboards and pointing devices. The DT-5K-NI features an integrated HulaPoint™ pointing device, and is enclosed in a stainless steel case. It also carries a Factory Mutual approval of Class I, Division II. These units do not require barriers and are ideal for harsh working conditions. All PS/2 units ship with bulkhead cables.

#### Features:

- 10-Key Numeric Pad
- Integrated HulaPoint™ Pointing Device
- Optional Mounting Holes Available
- PS/2 or USB configurations available

### Product Code DT-5K-NI

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B, Factory Mutual Class I, Division II, Groups A, B, C and D
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: 2 separate cables on PS/2 or single-cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
Weight	5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	16.25" x 7.88" x 1.8" (w-h-d) 412.8mm x 200.2mm 45.7mm
Model Numbers	DT-5K-NI-PS2: With PS/2 cable DT-5K-NI-USB: With USB cable



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

