



DT-5K

KEYBOARD WITH INTEGRATED HULAPOINT II™

The DT-5K combines HulaPoint II™ an upgraded pointing device that offers improved sensitivity and increased durability, with a 10-key numeric keypad in a ruggedized stainless steel case, providing dual functionality in one compact unit. Its 20 function keys provide user versatility. This keyboard also offers user Windows keys for ease of access to the operating system.

- Features:
- 10-Key Numeric Pad
 - 113-Key Functionality
 - 20 Function Keys
 - Integrated HulaPoint II™ Pointing Device
 - USB, PS/2 and AT Configurations Available

Product Code DT-5K

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 7.03 oz +/- 1.06 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2 or AT/Serial: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	16.25" x 7.88" x 1.80" (w-h-d) 412.8mm x 200.2mm x 45.7mm
MODEL NUMBERS	DT-5K-PS2: With PS/2 cable DT-5K-USB: With USB cable DT-5K-STD: With AT/serial cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

