



DT-810-TB

KEYBOARD WITH INTEGRATED TRACKBALL

The DT-810-TB is constructed using a highly rugged, stainless steel case and industrial silicone rubber pad. The DT-810-TB's trackball pointing device is a completely sealed 25-mm unit. The trackball is operated using sealed stainless steel switches with left, right and middle click functions.

- Features:
- 12 Function Keys
 - Integrated Trackball
 - Fn Key for secondary legend
 - PS2 or USB available

Product Code DT-810-TB

Related Products DBL-810-TB

CERTIFICATIONS	NEMA 4X
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or USB cable
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: KEYBOARD: 50mA@5V (from Keyboard port) TRACKBALL: 20mA@5V (from Mouse port) USB: 70mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD/TRACKBALL: All Windows Operating Systems USB KEYBOARD/TRACKBALL: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +85C (-40F to +185F) OPERATING: 0C to +65C (+32F to +149F)
WEIGHT	4.25 lbs +/- 0.10 lbs (1.81 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	14.80" x 5.72" x 1.69" (w-h-d) 376mm x 144.3mm x 42.9mm
MODEL NUMBERS	DT-810-TB-PS2: With PS/2 cable DT-810-TB-USB: With USB cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

