



DU-5K-NI

NONINCENDIVE KEYBOARD WITH HULAPOINT II™

iKey manufactures devices to reduce risk of failure in your hazardous areas. The nonincendive DU-5K-NI is designed to meet NEMA 4X specifications. It features 116-key functionality, including 24 function keys, and an ABS polycarbonate case. It has a Factory Mutual approval of Class I, Division II. These units do not require barriers and are ideal for harsh working conditions. An upgraded HulaPoint II™ pointing device is integrated into the DU-5K-NI, which offers improved sensitivity and increased durability. All units ship with bulkhead cables.

Features:

10-Key Numeric Pad
116-Key Functionality
24 Function Keys
Integrated HulaPoint II™ Pointing Device
Polycarbonate Case with Mounting Holes
PS/2 or USB configurations available

Product Code DU-5K-NI

Related Products DU-5K, DU-5K-IS

CERTIFICATIONS	NEMA 4X, UL60950, FCC Part 15 Class B Factory Mutual Class I, Division II, Gas Groups C, D, E, F, & G.
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: 2 separate cables on PS/2 or single-
	cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm)
	ACTUATION FORCE: 6.35 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF
	TEST PER AXIS: 3 hours
POWER	KEYBOARD: 5V@ 10 ma (from CPU port) HULAPOINT: 5V@ 10 ma (from mouse conn. port)
COMPATIBILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All
	Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	2.6 lbs +/- 0.10 lbs (1.7 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	14.94" x 6.63" x 1.81" (w-h-d) 379.5mm x 168.4mm x 46mm
MODEL NUMBERS	DU-5K-NI-PS2: With PS/2 cable DU-5K-NI-USB: With USB cable



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

