



## DU-5K

### DESKTOP KEYBOARD WITH HULAPOINT II™

The DU-5K is designed to meet NEMA 4X specifications. It features an ABS polycarbonate case, 116 keys including 24 function keys, and a HulaPoint II™ pointing device. These features make the DU-5K a total solution in one convenient package.

#### Features:

- 10-Key Numeric Pad
- 116-Key Functionality
- Integrated HulaPoint II™ Pointing Device
- Polycarbonate Case with Mounting Holes
- USB, PS/2 and AT/serial configurations available

## Product Code DU-5K

CERTIFICATIONS	NEMA 4X, UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35 oz. +/- 1.06 oz. (180g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2 or AT/Serial: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100%
DIMENSIONS	14.94" x 6.63" x 1.81" (w-h-d) 379.5mm x 168.4mm x 45.9mm
MODEL NUMBERS	DU-5K-PS2: With PS/2 cable DU-5K-USB: With USB cable DU-5K-STD: With AT/serial cable



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

