

## FT-88-911-TP

### BACKLIT KEYBOARD WITH INTEGRATED TOUCHPAD



The FT-88-911-TP is designed for vehicle mount in emergency, police, service, transport trucks and marine vessels. With a full-travel keystroke, the FT-88-911-TP feels like a regular keyboard while maintaining the rugged standards of all iKey products. Ideal for in-vehicle use, the FT-88-911-TP features red LED backlit keys for low-light environments, a one-touch emergency key and an integrated touchpad.

- Features**
- 12 Function Keys
  - 88-Key Functionality
  - Integrated Backlighting
  - Integrated Touchpad
  - Mobile Mounting Holes
  - One-Touch Emergency Key

## Product Code FT-88-911-TP

CERTIFICATIONS	UL60950, CE, FCC Part 15, Class B, NEMA 4
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 ft coiled (1.2m) DESIGN: Swappable PS/2-Y (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: ABS Polycarbonate plastic LIFE: Greater than 10 million cycles TRAVEL: 0.120 in. (3.0mm) ACTUATION FORCE: 2.20 oz +/- 0.18 oz (62.39g +/- 5g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: KEYBOARD: 315mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 325mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
TEMPERATURE RANGE	Storage -40C to +90C (-40F to +194F) Operating -40C to +70C (-40F to +158F)
WEIGHT	2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100%
DIMENSIONS	11.94" x 7.69" x 1.20" (w-h-d) 303.3mm x 195.3mm x 30.5mm
MODEL NUMBERS	FT-88-911-TP-PS2: With PS/2 cable FT-88-911-TP-USB: With USB cable



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

