

HP-OEM

OEM HULAPOINT II™ INDUSTRIAL POINTING DEVICE



The OEM version of the HulaPoint II™ industrial pointing device offers the same functionality as the enclosed HulaPoint II™. The low-profile design contains no protruding parts that might break and no moving elements to collect dust. With its completely sealed NEMA 4X design, the HulaPoint II™ can withstand spills, washdowns, contaminants and the impacts of an industrial environment.

Features

OEM Kit: PCB, rubber overlay, and cable
USB, PS/2 and AT/serial configurations available

Product Code HP-OEM

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: PS/2, Serial or USB Cable
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: POINTER: 35mA@5V (Mouse port) USB: 35mA@5V (CPU port)
COMPATIBILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to 158F) OPERATING: -20C to +60C (-4F to 140F)
WEIGHT	0.5 lb (0.23 kg)
WARRANTY	90 day limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	3.70" x 3.70" x 0.54" (w-h-d) 94mm x 94mm x 13.7mm
MODEL NUMBERS	HP-OEM-PS2: With PS/2 cable HP-OEM-USB: With USB cable HP-OEM-STD: With serial cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

