

HP-PM-NI

NONINCENDIVE PANEL MOUNT HULAPOINT II™ POINTING DEVICE



iKey manufactures devices to reduce risk of failure in your hazardous areas. The nonincendive HP-PM-NI features the HulaPoint II™, an upgraded pointing device that offers improved sensitivity and increased durability. The low-profile design contains no protruding parts that might break and no moving elements to collect dust. With its completely sealed NEMA 4X design, the HulaPoint II™ can withstand spills, washdowns, contaminants and the impacts of an industrial environment. The HP-PM-NI has a Factory Mutual approval for Class I, Division II, Groups A, B, C, and D.

Features:

- Nonincendive for use in hazardous locations
- PS/2 or USB configurations available
- Stainless Steel Bezel

Product Code HP-PM-NI

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B Factory Mutual Class I, Division II, Groups A, B, C, and D
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	5 feet (1.5 m) from keyboard to Bulkhead Connector
KEY SWITCH	5 feet (1.5 m) from keyboard to Bulkhead Connector
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 KHz DURATION OF TEST PER AXIS: 3 hours
COMPATIBILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to 158F) OPERATING: -20C to +60C (-4F to 140F)
WEIGHT	1.25 lbs (0.57 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant (when properly installed)
DIMENSIONS	6.0" x 6.0" x 1.12" (w-h-d) 152.4mm x 152.4mm x 28.4mm
MODEL NUMBERS	HP-PM-NI-PS2: With PS/2 cable HP-PM-NI-USB: With USB cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

