



PM-1000-IS

INTRINSICALLY SAFE STAINLESS STEEL PANEL MOUNT KEYBOARD



iKey manufactures devices to reduce risk of failure in your hazardous areas. The intrinsically safe PM-1000-IS is framed in stainless steel to ensure optimal durability and waterproof functionality. It is designed to meet NEMA 4X specifications, which enables it to survive in the roughest of conditions. The PM-1000-IS has a Factory Mutual approval for Class I, II and III, Division I, Groups C, D, E, F and G. The unit includes optical isolated barriers and bulkhead cables for complete protection in hazardous locations.

- Features:
- 10-Key Numeric Pad
 - 114-Key Functionality
 - 24 Function Keys
 - PS/2 configurations available

Product Code PM-1000-IS

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B Factory Mutual Class I, II, & III, Division I, Groups C, D, E, F, & G
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: 2 separate cables
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	5.6 lbs +/- 0.10 lbs (2.54 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	17.70" x 9.20" x 1.58" (w-h-d) 449.6mm x 233.7 mm x 40.1 mm
MODEL NUMBERS	PM-1000-IS: With PS/2 cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

