

PM-1000-NI

NONINCENDIVE STAINLESS STEEL PANEL MOUNT KEYBOARD



iKey offers a full line of nonincendive keyboards and pointing devices. The nonincendive PM-1000-NI is framed in stainless steel to ensure optimal durability and waterproof functionality. It is designed to meet NEMA 4X specifications, which enables it to survive in the roughest of conditions. The PM-1000-NI has a Factory Mutual approval of Class I, Division II. These units do not require barriers and are ideal for harsh working conditions. All units ship with bulkhead cables.

Features:

- 10-Key Numeric Pad
- 114-Key Functionality
- 24 Function Keys
- PS/2 or USB configurations available

Product Code PM-1000-NI

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B Factory Mutual Class I, Division II
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: 2 separate cables on PS/2 or single-cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	5 lbs +/- 0.10 lbs (2.54 kg +/- 0.05kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	17.70" x 9.20" x 1.58" (w-h-d) 449.6mm x 233.7 mm x 40.1mm
MODEL NUMBERS	PM-1000-NI-PS2: With PS/2 cable PM-1000-NI-USB: With USB cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

