



PM-1000

STAINLESS STEEL PANEL MOUNT KEYBOARD

iKey's rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. The PM-1000 is framed in stainless steel to ensure optimal durability and waterproof functionality. It is designed to meet NEMA 4X specifications, which enables it to withstand the roughest of conditions.

Features:

10-Key Numeric Pad 114-Key Functionality 24 Function Keys USB, PS/2 and AT Configurations Available

Product Code PM-1000

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: PS/2, AT or Single-Cable USB
	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in.
KEY SWITCH	(1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with
	Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF
	TEST PER AXIS: 3 hours
POWER	PS/2 or AT: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh
COMI ATABILITT	OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	17.70" x 9.20" x 1.58" (w-h-d) 449.6mm x 233.7 mm x 40.1 mm
MODEL NUMBERS	PM-1000-PS2: With PS/2 cable PM-1000-USB: With USB cable PM-1000-STD: With AT cable



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

