



PM-1000

STAINLESS STEEL PANEL MOUNT KEYBOARD

iKey's rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. The PM-1000 is framed in stainless steel to ensure optimal durability and waterproof functionality. It is designed to meet NEMA 4X specifications, which enables it to withstand the roughest of conditions.

Features:

- 10-Key Numeric Pad
- 114-Key Functionality
- 24 Function Keys
- USB, PS/2 and AT Configurations Available

Product Code PM-1000

| | |
|-------------------|--|
| CERTIFICATIONS | NEMA 4X UL60950, FCC Part 15 Class B |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 10 feet (3 meters) DESIGN: PS/2, AT or Single-Cable USB |
| KEY SWITCH | MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS/2 or AT: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port) |
| COMPATABILITY | PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) |
| WEIGHT | 5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg) |
| WARRANTY | 1 year limited warranty |
| HUMIDITY | 100% (when properly installed) |
| DIMENSIONS | 17.70" x 9.20" x 1.58" (w-h-d) 449.6mm x 233.7 mm x 40.1 mm |
| MODEL NUMBERS | PM-1000-PS2: With PS/2 cable PM-1000-USB: With USB cable PM-1000-STD: With AT cable |



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

