

## PM-102-SS

### PANEL MOUNT STAINLESS STEEL KEYBOARD WITH TOUCHPAD



iKey has combined the convenience of a panel-mounted, touchpad keyboard with the rugged strength of stainless steel in the new PM-102-SS industrial keyboard. Stainless steel is known for its longevity, corrosion resistance and ability to retain strength in extreme temperatures. It's also low-maintenance and easy to clean. Each of these characteristics make stainless steel an excellent material for keyboards used in industrial and food processing applications. The durable PM-102-SS is completely sealed and designed to meet NEMA 4X and IP66 specifications when properly installed.

#### Features:

- Integrated Touchpad
- Low-profile stainless steel keys
- PS/2 or USB configurations available
- Stainless Steel Bezel

## Product Code PM-102-SS

CERTIFICATIONS	NEMA 4X, IP66
SHOCK	3 x 11 ms pulses of 50g on each of 3 axes
KEY SWITCH	MATERIAL: Brushed Stainless Steel LIFE: Greater than 10 Million Cycles TRAVEL: 0.079 in. (2mm) ACTUATION FORCE: 4.23 oz. +/- 0.18 oz. (120g +/- 5g)
VIBRATION	POWER SPECTRAL DENSITY: .04g <sup>2</sup> /HZ FREQUENCY OF RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 60mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +65C (-40F to +149F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	5.00 lbs +/- 0.10 lbs (2.27 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	17.700" x 9.020" x 1.575" (w-h-d) 449.6mm x 229.1mm x 40.0mm
MODEL NUMBERS	PM-102-SS-PS2: With PS/2 Cable PM-102-SS-USB: With USB Cable



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

