



PM-18-HP

NUMERIC KEYPAD WITH HULAPOINT™

The PM-18-HP provides a full numeric keypad that is easily integrated into any system. The secondary legend can be accessed by pressing the NumLock key. The PM-18-HP further increases its versatility with the two-button HulaPoint™ industrial pointing device. It is also possible to cascade a secondary keyboard if needed.

Features:

- Integrated HulaPoint™ Pointing Device
- Numlock Key for Secondary Keyboard
- USB, PS/2 and AT/serial configurations available

Product Code PM-18-HP

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse connections)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 4.74 oz. +/- 1.06 oz. (135g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2 and USB KEYBOARD: 40mA@5V (from Keyboard port) PS/2 and USB POINTER: 10mA@5V (from Mouse port)
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +65C (-40F to +149F) OPERATING: -0C to +60C (+32F to +140F)
WEIGHT	2.00 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	5.85" x 8.51" x 0.31" (w-h-d) 148.6mm x 216.2mm x 7.9mm SCREWS: 0.50" (12.7mm)
MODEL NUMBERS	PM-18-PS2: With PS/2 cable PM-18-STD: With AT/serial cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

