

PM-18

PANEL MOUNT NUMERIC KEYPAD



The PM-18 is an 18-key numeric pad that is protected in a stainless steel case and is easily integrated into any system. When properly sealed, the PM-18 is engineered to meet NEMA 4X specifications. It features navigation keys and the secondary legend can be accessed by pressing the NumLock key. It is also possible to cascade a secondary keyboard if necessary.

Features:

- Numlock Key for Secondary Keyboard
- Stainless Steel Bezel
- USB, PS/2 and AT Configurations Available

Product Code PM-18

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: PS/2 or AT Cable
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 4.74 oz. +/- 1.06 oz. (135g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to 70C (-40F to +158F)
WEIGHT	1.00 lbs +/- 0.10 lbs (0.92 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	5.85" x 7.05" x 0.20" (w-h-d) 148.6mm 179.1mm x 5.1mm SCREWS: 0.50" (12.7mm) CUTOUT: 4.50" x 5.30" (w-h) 114.3mm x 134.6mm
MODEL NUMBERS	PM-18-PS2: With PS/2 cable PM-18-USB: With USB cable PM-18-STD: With AT cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

