



PM-2000

PANEL MOUNT KEYBOARD WITH HULAPOINT II™

The PM-2000 is constructed using a highly rugged stainless steel case and industrial silicone rubber pad, ensuring NEMA 4X protection in extremely rugged applications. An integrated HulaPoint II™ pointing device offers additional usability. The PM-2000 provides users with a full 114-key industrial keyboard and HulaPoint II™ industrial pointing device. It has two rows of function keys that allow for single keystroke access to software shortcuts.

Features:
10-Key Numeric Pad
24 Function Keys
Integrated HulaPoint II™ Pointing Device
USB, PS/2 and AT/serial configurations available

Product Code PM-2000

| CERTIFICATIONS | NEMA 4X, CE UL60950, FCC Part 15 Class B |
|-------------------|---|
| SHOCK | 3x11 ms pulses of 50g on each of 3 axis |
| CABLE | LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and |
| | mouse connections), or Single-Cable USB |
| KEY SWITCH | MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. |
| | (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with |
| | Mechanical Snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST |
| | PER AXIS: 3 hours |
| POWER | PS/2 or AT/serial: KEYBOARD: 50mA@5V (from Keyboard port), POINTER: 35mA@5V (from Mouse |
| | port); USB: 85mA@5V (from CPU port) |
| COMPATABILITY | PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All |
| | Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F) |
| WEIGHT | 5.50 lbs +/- 0.10 lbs (2.49 kg +/- 0.05 kg) |
| WARRANTY | 1 year limited warranty |
| HUMIDITY | 100% (when properly installed) |
| DIMENSIONS | 21.80" x 9.20" x 0.28" (w-h-d) 553.7mm x 233.7mm x 7.1mm SCREWS: 1.58" (40.1mm) |
| MODEL NUMBERS | PM-2000-PS2: With PS/2 cable PM-2000-USB: With USB cable PM-2000-STD: With AT/serial cable |
| | |



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

