



PM-5K

PANEL MOUNT KEYBOARD WITH HULAPOINT II™

The PM-5K combines a HulaPoint II™ pointing device and a 10-key numeric keypad in a ruggedized stainless steel case to provide dual functionality. This keyboard also offers user Windows keys for ease of access to the operating system. Its integrated HulaPoint II™ pointing device makes the PM-5K a total solution in one convenient package.

Features:

- 10-Key Numeric Pad
- 20 Function Keys
- Integrated HulaPoint II™ Pointing Device
- USB, PS/2 and AT/serial configurations available

Product Code PM-5K

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2 or AT/Serial: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	17.70" x 9.20" x 1.58" (w-h-d) 449.6mm x 233.7mm x 40.1mm
MODEL NUMBERS	PM-5K-PS2: With PS/2 cable PM-5K-USB: With USB cable PM-5K-STD: With AT/serial cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

