



PM-72

PANEL MOUNT KEYBOARD WITH OVERSIZED KEYS

iKey's innovative PM-72 panel mount keyboard was designed to accommodate rugged applications in manufacturing, material handling and remote data entry. Its unique, oversize keys are color arranged and feature a roomy layout for convenient gloved-hand use. It features a small-footprint design and a large numeric pad. Like other keyboards in the iKey line, the PM-72 is constructed with an industrial silicone keypad, sealing it from dust, liquids and corrosives.

Features: 72-Key Functionality 8 Function Keys USB and PS/2 configurations available

Product Code PM-72

| CERTIFICATIONS | NEMA 4X UL60950, FCC Part 15 Class B |
|-------------------|---|
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 4 ft coiled (1.2m) DESIGN: PS/2 or USB Cable |
| KEY SWITCH | MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. |
| | (1.4mm) ACTUATION FORCE: 4.74 oz. +/- 0.70 oz. (135g +/- 20g) FEEDBACK: Tactile with |
| | Mechanical Snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF |
| | TEST PER AXIS: 3 hours |
| POWER | PS/2: KEYBOARD: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port) |
| COMPATIBILITY | PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh |
| | OS |
| TEMPERATURE RANGE | STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) |
| WEIGHT | 1.75 lbs +/- 0.10 lbs (0.80 kg +/- 0.05 kg) |
| WARRANTY | 1 year limited warranty |
| HUMIDITY | 100% |
| DIMENSIONS | 11.80" x 6.79" x 1.36" (w-h-d) 299.7mm x 172.5mm x 34.5mm |
| MODEL NUMBERS | PM-72-PS2: With PS/2 cable PM-72-USB: With USB cable |
| | |



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

