

PM-TB

PANEL MOUNT INDUSTRIAL OPTICAL TRACKBALL



The new panel mount PM-TB offers solid-state laser trackball technology in a completely sealed and waterproof enclosure. Designed to meet NEMA 4X protection, the PM-TB's 38-mm trackball sits inside polycarbonate housing with stainless steel bezels. The trackball is easily removable for convenience cleaning, while an adjustable tension ring ensures the proper amount of trackball smoothness for any user. In addition, the PM-TB features sealed stainless steel switches, including a programmable button. The PM-TB is ESD-safe, and available with the choice of either PS/2 or USB cables.

- Features:
- Adjustable Tension Ring
 - ESD Safe
 - PS/2 or USB configurations available
 - Removable Ball
 - Stainless Steel Bezel

Product Code PM-TB

| | |
|-------------------|---------------------------------------------------------------------------------------------------|
| CERTIFICATIONS | NEMA 4X, CE UL60950, FCC Part 15 Class B |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 10' straight (3 m) DESIGN: PS/2 or USB Cables |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS/2: 45mA@5V (from Mouse port) USB: 45mA@5V (from CPU port) |
| COMPATIBILITY | PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +85C (-40F to 185F) OPERATING: 0C to +55C (32F to 131F) |
| WEIGHT | 2.25 lbs (1.02 kg) |
| WARRANTY | 1 year limited warranty |
| DIMENSIONS | 6.0" x 6.0" x 1.78" (w-h-d) 152.4mm x 152.4mm x 45.2mm |
| MODEL NUMBERS | PM-TB-PS/2: with PS/2 cable PM-TB-USB with USB Cable |



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

