



SL-75-OEM

OEM COMPACT KEYBOARD

The compact SL-75-OEM is excellent for integration into industrial and mobile applications. This rugged keyboard is designed to meet NEMA 4X specifications when properly installed. The SL-75-OEM kit includes an industrial silicone rubber pad, board and cable. The SL-75-OEM features red LED backlit keys for use in areas with minimal lighting and 75 keys, including 12 function keys.

Features:

Red Backlit Keys

USB, PS/2 and AT/serial configurations available

Product Code SL-75-OEM

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3 x 11 ms pulses of 50g on each of 3 axis
CABLE	LENGTH: 10 feet straight (3 m)
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 4.76 oz. (135g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C OPERATING: -40C to +70C
WEIGHT	.75 lbs (0.34 kg)
WARRANTY	90 Day Limited Warranty
HUMIDITY	100% Humidity Resistant (when properly installed)
DIMENSIONS	7.85" x 3.85" x 0.36" (w-h-d) 199.4 x 97.8 x 9.1 mm
MODEL NUMBERS	SL-75-OEM-PS2: With PS/2 Cable SL-75-OEM-USB: With USB Cable SL-75-OEM-STD: With AT/Serial Cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

