



SL-75

COMPACT MOBILE KEYBOARD

The compact SL-75 is excellent in mobile applications where there is limited space available. This rugged keyboard is designed to meet NEMA 4X specifications. It is built with an industrial silicone rubber keypad and a black aluminum case. The SL-75 features red LED backlit keys for use in areas with minimal lighting and 75 keys, including 12 function keys.

Features:

Red Backlit Keys

USB, PS/2 and AT/serial configurations available

Product Code SL-75

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3 x 11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet straight (3 m)
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 4.76 oz. +/- 1.06 oz (135g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	1.25 lbs +/- 0.10 lbs (0.57 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	8.25" x 4.34" x 1.08" (w-h-d) 209.6 x 110.2 x 27.4
MODEL NUMBERS	SL-75-PS2: With PS/2 Cable SL-75-USB: With USB Cable SL-75-STD: With AT/Serial Cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

