



## SL-86-911-OEM

## OEM KEYBOARD FOR PUBLIC SAFETY

The SL-86-911-OEM offers both a rugged keyboard and rugged computer pointing device in one compact package. Ideal for public safety applications, it features a specially designed emergency key that, when pressed, sends a signal of Shift+F1 and lights up for 30 seconds. Compactly designed with mounting holes, the SL-86-911 - OEM fits securely in a vehicle's console to ensure efficiency as a mobile application. It is designed to meet NEMA 4X specifications when properly sealed, ensuring that this keyboard is sealed against the elements or unwanted spills.

Features:
86-Key Functionality
Integrated Backlighting
Integrated HulaPoint II™ Pointing Device
OEM Kit: PCB, rubber overlay, and cable
One-Touch Emergency Key
USB and PS/2 configurations available

## Product Code SL-86-911-OEM

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 feet coiled (1.2 m) DESIGN: "Y" PS/2 (providing separate keyboard and mouse
	connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE:
	200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF
	TEST PER AXIS: 3 hours
POWER	KEYBOARD: 200mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB:
	235mA@5V (from CPU port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT:
	All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C OPERATING: -20C to +60C
WEIGHT	2 lbs (0.92 kg)
WARRANTY	90 day limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	11.12" x 6.05" x 0.72" (w-h-d) 282.4mm x 153.7mm x 18.3mm
MODEL NUMBERS	SL-86-911-OEM-PS2: With PS/2 cable SL-86-911-OEM-USB: With USB cable



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

