

SL-88-OEM

OEM COMPACT BACKLIT INDUSTRIAL KEYBOARD



The SL-88-OEM, when properly installed, is designed to meet NEMA 4X specifications and is ideal for industrial, kiosk and mobile computing applications. It is a compact keyboard featuring red LED backlit keys and an industrial silicone rubber keypad. The SL-88-OEM has a secondary legend accessed with the NumLock and Fn key.

Features:

- 12 Function Keys
- 88-Key Functionality
- Integrated Backlighting
- USB and PS/2 configurations available

Product Code SL-88-OEM

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10' straight (3 m)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from USB port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C OPERATING: -40C to +70C
WEIGHT	1 lbs (0.45 kg)
WARRANTY	90 day limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	11.12" x 6.05" x 0.72" (w-h-d) 282.5mm x 153.7mm x 18.3mm
MODEL NUMBERS	SL-88-OEM-PS2: With PS/2 cable SL-88-OEM-USB: With USB cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

