



SLK-880-FSR-OEM

MILITARY KEYBOARD WITH ADJUSTABLE BACKLIGHTING

The SLK-880-FSR-OEM exceeds NEMA 4X requirements when properly installed and is fully-submersible, meeting IP68 specifications. Unique features of the SLK-880-FSR-OEM include a conductive plastic case, adjustable green backlighting that is also available in a night vision (NVIS) compatible configuration, and an integrated Interlink Electronics Force Sensing Resistor (FSR) pointing device.

Features:

- Adjustable backlighting
- Integrated FSR pointing device
- Optional NVIS Compliant – Green B backlighting

Product Code SLK-880-FSR-OEM

Certifications	UL60950
Shock	3 X 11 ms pulses of 50g on each of 3 axis
Cable	6 ft. straight (1.8 m)
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. ACTUATION FORCE: 6.35 oz. +/- 0.71 oz (180g +/- 20g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Power	USB: 300mA@5V (from CPU port)
Compatibility	USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40F to +167F (-40C to +75C) OPERATING: -40F to +158F (-40C to +70C)
Weight	1.75 lbs +/- 0.10 lbs (0.79 kg +/- 0.05 kg)
Warranty	1 Year Limited
Humidity	100% Humidity Resistant
Dimensions	11.23" x 6.62" x 0.17" (w-h-d) 285.2mm x 168.1mm x 4.3 mm
Model Number	SL-880-FSR-OEM-USB: With USB Cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

