

uHP-1535

INDUSTRIAL HULAPOINT™ POINTING DEVICE

The uHP-1535 is a smaller version of our regular HulaPoint™. The two-button device offers the versatility and convenience of the HulaPoint™ but in a compact version to suit the needs of industrial laptops and workstations. Like all of iKey's products, the sealed design means the uHP-1535 is dustproof, waterproof and non-corrosive.

AT/Serial and PS/2 configurations available
OEM Kit: PCB, rubber overlay, and cable

Features:
AT/Serial and PS/2 configurations available
OEM Kit: PCB, rubber overlay, and cable



Product Code uHP-1535

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 6ft (1.8 m)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2 HULAPOINT: 5V@ 10 ma (from mouse conn. port)
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems SERIAL HULAPOINT: All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to 194F) OPERATING: -40C to +70C (-40F to 158F)
WEIGHT	1 lb (.46 kg)
WARRANTY	90 day limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	3.5" x 1.5" x 0.5" (w-h-d)



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

