

Dolphin 99EX

Mobile Computer

Purpose built for transportation and logistics applications, Honeywell's Dolphin® 99EX mobile computer provides user-friendly ergonomics, cutting-edge wireless technology, multi-functional data capture and extreme durability for front-line workers operating in a variety of locations ranging from loading docks to residential doorsteps.

The reliable and intuitive Dolphin 99EX delivers an outstanding feature set that enables improved productivity for mobile workers. Integrated Shift-PLUS™ technology provides all day battery life, minimizing the time and expense incurred when batteries need to be charged or replaced. The Dolphin 99EX is IP67-rated and can withstand multiple 6 feet (1.8 meters) drops to concrete, ensuring years of trouble-free operation.

The 99EX features the latest in wireless technology, including a software-definable radio that allows on-the-fly switching between GSM and CDMA networks, leading to improved network coverage and lower costs related to device provisioning and deployment. Additionally, built-in Wi-Fi provides workers with access to critical data using the new, lightning fast 802.11n standard while still supporting legacy a/b/g protocols.

Integrated motion, light and proximity sensors help conserve battery life and improve ease of use by automatically optimizing the offering for the current environment. Similarly, multiple keypad options are available to ensure that the device is configured to meet diverse data input needs. With additional features such as an ultra-bright 3.7 inch display that can be read, even in direct sunlight, the Dolphin 99EX offers superior usability.

Designed with input from leading companies in the transportation and logistics sector, Honeywell's Dolphin 99EX mobile computer provides a rugged solution that increases productivity by connecting enterprises, front-line workers and customers using real-time wireless communication.



Features

- Superior Durability: Incorporates an IP67-rated design that withstands multiple 6 feet drops to concrete and 2,000 1 meter tumbles, resulting in a lower total cost of ownership for enterprises
- Shift-PLUS Power Management: Enhances productivity by providing full shift battery life, eliminating the need for employees to carry spare batteries or chargers
- Adaptus® Imaging Technology 6.0: Enables multifunctional data capture by providing fast scanning of linear and 2D bar codes with excellent motion tolerance, as well as seamless image capture through use of an integrated color camera
- Fast and Reliable Wireless Connectivity: Delivers full
 wireless coverage for applications inside and outside of the
 four walls, allowing real-time access to critical data
- Optimal Combination of Performance and Usability: Improves ease of use and worker efficiency with a large outdoor-viewable screen, multiple keypad options, a super fast CPU and smart sensors
- Optional Remote MasterMind® Software Package:
 Extends mobile workforce capabilities and reduces total cost of ownership by providing a turnkey remote device management solution
- Optional Service Made Simple™ Service Plans: Offers comprehensive, hassle-free protection on the device investment for up to five years after purchase

Dolphin 99EX Technical Specifications

1.5" L x 2.7" W (keypad) x 1.5" (standard battery)/1.8" (extended battery) 15 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery) 15 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery) 15 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery) 15 tandard battery – 520g (18.3 oz.); Extended battery – 570g (20.1 oz.) 15 to 158°F (-25° to 70°C) 13° to 158°F (-25° to 70°C) 15% humidity, non-condensing 15 this tands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range 15 taxceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification 16 the pendently certified to meet IP67 standards for moisture and particle resistance 16 this tandards for moisture and particle resistance 17 this tax 15 kV; Contact: ±8 kV 18 this tax 256 MB RAM 18 the mically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits 18 the dustrial touch panel with resistive touch and support for finger touch and stylus
4° to 122°F (-20° to 50°C) 13° to 158°F (-25° to 70°C) 5% humidity, non-condensing Withstands multiple 6′ (1.8m) drops to concrete, all axis, and across operating temperature range Exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification Independently certified to meet IP67 standards for moisture and particle resistance In: ±15 KV; Contact: ±8 KV Exact Instruments® OMAP3715 1.0GHz processor Incrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7″ transflective active matrix glass display, VGA (480x640), 333 nits
13° to 158°F (-25° to 70°C) 5% humidity, non-condensing Withstands multiple 6′ (1.8m) drops to concrete, all axis, and across operating temperature range exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification Independently certified to meet IP67 standards for moisture and particle resistance In: ±15 KV; Contact: ±8 KV Exact Instruments® OMAP3715 1.0GHz processor Incrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7″ transflective active matrix glass display, VGA (480x640), 333 nits
5% humidity, non-condensing Withstands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle resistance Independently certified to meet IP67 standards for moisture and particle
Withstands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification adependently certified to meet IP67 standards for moisture and particle resistance air: ±15 KV; Contact: ±8 KV Exas Instruments® OMAP3715 1.0GHz processor Microsoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
Exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification independently certified to meet IP67 standards for moisture and particle resistance iir: ±15 KV; Contact: ±8 KV Exas Instruments® OMAP3715 1.0GHz processor Idicrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7″ transflective active matrix glass display, VGA (480x640), 333 nits
dependently certified to meet IP67 standards for moisture and particle resistance dir: ±15 KV; Contact: ±8 KV dexas Instruments® OMAP3715 1.0GHz processor dicrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7″ transflective active matrix glass display, VGA (480x640), 333 nits
exas Instruments® OMAP3715 1.0GHz processor flicrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
exas Instruments® OMAP3715 1.0GHz processor flicrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7″ transflective active matrix glass display, VGA (480x640), 333 nits
dicrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
dicrosoft® Windows Embedded Handheld 6.5 Professional and Classic GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
GB discrete NAND flash x 256 MB RAM Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
ndustrial touch panel with resistive touch and support for finger touch and stylus
radothar todor parior war rodotto todor and dapport for linger todor and digital
acklit 55-key alphanumeric, 43-key alpha shifted numeric, 34-key numeric shifted alpha (phone or calculator style
peaker, HAC compliant receiver, microphone
.1 megapixel camera with Automated Camera Control (ACC). Features include automated picture profiles, cam pplication Programming Interface (API), cooperational use of camera and imager, and flashlight utility
S-232/USB 2.0/audio out/charging connector, integrated IrDA port with support for SIR mode
flicroSD card (support for up to 32GB)
standard – Li-ion, 3.7V, 3060mAh; Extended – Li-ion, 3.7V, 5000mAh
standard/Extended: 9 hours/15.5 hours (scanning and sending data over WLAN every 9 seconds) standard/Extended: 8 hours/14.75 hours (scanning and sending data over WWAN every 15 seconds, GPS ontinuously receiving information)
l5600/5603 Standard range (SR), Extended range (ER), and High Density (HD) imagers with high-visibility lase r green LED aimer. All imagers have 25° angle and come equipped with Adaptus 6.0 Imaging Technology
leads standard 1D and 2D symbologies
Ioneywell SDK for Windows® Embedded
year factory warranty
optional three-and five-year Service Made Simple programs offer worry-free mobile computing
oftware definable Gobi 3000 (data only) 3.75G radio with five-band UMTS/HSPA+ (800/850/900/1900/2100MF uadband GSM/GPRS/EDGE (850/900/1800/1900MHz) and dual-band EV-DO/CDMA (800/1900) support for ual SIM card oice and data 3.75G radio with five-band UMTS/HSPA+ (800/850/900/1900/2100MHz) and quad-band GSM/GPRS/EDGE (850/900/1800/1900MHz)
02.11a/b/g/n, Wi-Fi™ - certified
VPA, WPA2 (Personal and Enterprise), 802.11x, EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, WMM, CWG-RF Profile, CCX v.4, WAPI
luetooth® V2.1, support for enhanced data rate 2.0 Mbps & 3.0 Mbps rates class II
Militate to the terminal of th

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies

















For more information:

www.honeywellaidc.com



9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com







www.L-TronDirect.com 800-830-9523 info@L-Tron.com

