






# PC23d PC43d PC43t

## Accessory Guide

### Connectivity

Accessory Name	Part Number	Description
 USB to Serial Adapter	203-182-100	<p>The USB to RS-232 adapter connects to the printer USB host (type A) port and provides serial RS-232 (female DB9) connectivity. Cable length is 1.8m. Serial flow control: XON/XOFF, RTS/CTS. (All models, RoHS)</p>
 USB to Parallel Adapter	203-182-110	<p>The USB to Parallel adapter connects to the printer USB host (type A) port and provides Parallel (DB25) connectivity. Cable length is 1.8m. Operation modes: Compatibility, Nibble, Byte. (All models, RoHS)</p>
 USB-A to USB-B Cable	321-576-004	<p>The USB-A to USB-B cable connects the printer device port (type B) to a PC host port (type A) to provide USB connectivity. Cable length is 2m. (All models, RoHS)</p> <p>Note: The USB cable ships standard with each printer.</p>
 Wi-Fi / BT Module	203-183-420	<p>The user installable Wi-Fi (802.11 b,g,n) / BT dual radio module provides both WLAN and Bluetooth(TM) connectivity. (All models, RoHS)</p> <p>The Wi-Fi radio supports static (64/128 bits) and dynamic WEP, WPA, WPA2, EAP-PEAP, EAP-TTLS, LEAP, EAP-FAST and EAP-TLS security protocols and is CCX version 3 compliant.</p> <p>The Bluetooth radio is v2.1+EDR, Class 2</p>
 Ethernet (IEEE 802.3) Module	203-183-210 (PC23d) 203-183-410 (PC43d, PC43t)	<p>The user installable IEEE 802.3 Ethernet module installs on the back of the printer (in place of the cover plate) and supports 10Base-T and 100Base-TX LAN communications. RJ45 CAT 5 cables up to 100m in length are supported. (PC23 Ethernet module has light case and PC43 Ethernet module has dark case, RoHS).</p> <p>Network Protocols Supported: TCP/IP, FTP, SNMP, LPR, HTTP.</p>

# PC23d PC43d PC43t

## Accessory Guide

### Media

Accessory Name	Part Number	Description
 Cutter	203-184-420 (PC43d) 203-184-520 (PC43t)	The user installable Cutter Module with label taken sensor (LTS) is programmable for full or partial cuts. (PC43d/t, RoHS)
 Cutter Tray (PC43d/t)	203-188-100	The user installable cutter tray holds up to 20 labels as they are cut. Attaches to the cutter unit. (PC43d/t)
 Label Dispenser (PC23d)	203-184-210	The user installable Label Dispenser Module with label taken sensor (LTS) strips off the paper backing to present only the label. (PC23d, RoHS)
 Label Dispenser (PC43d)	203-184-410	The user installable Label Dispenser Module with label taken sensor (LTS) strips off the paper backing to present only the label. (PC43d, RoHS)
 Label Dispenser (PC43t)	203-184-510	The user installable Label Dispenser Module with label taken sensor (LTS) strips off the paper backing to present only the label. (PC43t, RoHS)
 Linerless Platen Roller (PC43d/t)	203-185-400 (PC43d) 203-185-500 (PC43t)	User installable non-stick platen roller dispenses printed labels when you use linerless media stock. (PC43d/t)
 Printhead (PC23d)	201-031-220 (203dpi) 201-031-230 (300dpi)	User installable 203 or 300 dpi printhead can be installed on any PC23 printer. (PC23d, RoHS)
 Printhead (PC43d/t)	201-031-420 (203dpi) 201-031-430 (300dpi)	User installable 203 or 300 dpi printhead can be installed on any PC43 printer. (PC43d/t, RoHS)
 Media Cover Lock Bracket	203-188-200	The 2-piece user installable Media Cover Lock Bracket securely attaches to the top cover and bottom case to deter media removable. It accepts a standard lock (user supplied). (All models)


# PC23d PC43d PC43t

## Accessory Guide



Copyright © 2013 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. 612166-B 06/13

### Power

Accessory Name	Part Number	Description
Power Adapter Basebay (PC43d) 	203-187-410	The user installable Power Adapter Basebay attaches to the base of the printer and holds the power adapter (provided with printer). (PC43d, RoHS)
Battery Basebay (PC43d) 	203-187-420	The user installable Battery Basebay attaches to the base of the printer and holds the rechargeable battery (sold separately) to provide mobile printing. Must be attached to printer for charging. Uses power adapter provided with printer. (PC43d, RoHS)
Rechargeable Battery Pack (PC43d) 	203-186-100	The 2600 mAH Li-ION rechargeable Battery Pack installs in the Battery Basebay (sold separately) to provide mobile printing. (PC43d, RoHS)
AC Power Cord 	1-974028-025 1-974027-025 1-974029-020 321-471-002 586276 321-501-002 321-502-002 071918 1-974030-025	Americas RoHS Europe RoHS UK RoHS Italy RoHS Liechtenstein, Switzerland RoHS Denmark RoHS India, South Africa RoHS China RoHS Australia RoHS
Power Adapter 	203-186-200	The Universal Power Adapter (100-240V) supplies power to the printer and charges the optional battery.  Note: The Power Adapter ships standard with every printer. (All models, RoHS)
Cleaning Card 	1-110501-00	The Cleaning Card accessory removes adhesives or other contaminants from the printhead and platen roller. It is suggested that a cleaning card be used with each new roll of media. Box of 25 cleaning cards, 4.5 x 6". (All Intermec printer models)

### Summary Table

Model	Connectivity Cables	Wi-Fi / BT	Ethernet	Cutter	Cutter Tray	Dispenser	Linerless Platen Roller	Printhead	Media Cover Lock Bracket	Power Adapter Basebay	Battery Basebay/Battery
PC23	USB to Serial 203-182-100	203-183-420	IEEE 802.3 203-183-210	Not Available	Not Available	203-184-210	Not Available	203 dpi 201-031-220 300dpi 201-031-230	203-188-200	Not Available	Not Available
PC43d	USB to Parallel 203-182-110		IEEE 802.3 203-183-410	203-184-420	203-188-100	203-184-410	203-185-400	203dpi 201-031-420 300dpi 201-031-430		203-187-410	203-187-420/ 203-186-100
PC43t	USB-A to USB-B 321-576-004		203-184-520	203-184-510		203-185-500	Not Available	Not Available			



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

