



## HIGH PERFORMANCE IN-COUNTER SCANNER AND SCANNER/SCALE

The Magellan 8400 bi-optic scanner is the highest performance 5-sided POS scanner available today. The 8400 improves operational efficiency by achieving outstanding first-pass read rates, and represents the next step in value and checkout productivity from the Magellan family and Datalogic, breaking previous records of performance, reliability and value.

## CUSTOMIZE TO YOUR LIKING

The 8400 can be configured as either scanner or scanner/scale combination with Datalogic's exclusive, patented All-Weighs® scale platter to ensure accurate produce and bulk food weighing at the checkout. Two remote scale display options are available; a single display on a pole and a dual display on a single pole for applications requiring separate displays for the cashier and customer. Magellan 8400 models are available in three lengths: long, medium, and short (scanner only) to accommodate various POS configurations.



## SOFTWARE BENEFITS

FirstStrike® advanced software decoding algorithms provide the industry's best scanning speed and simultaneously improve first pass read rates of damaged, wrinkled, or poorly printed bar codes delivering improved operational efficiencies at the retail checkout.

Flash memory allows for easy software upgrades that help extend the life of the retailer's investment. In addition, an auxiliary RS-232 port can be utilized in a variety of ways, including adding a handheld scanner, programming and configuring the scanner, or accessing the scanner's label data output.

## FEATURES

- Aggressive and ergonomic 360° 5-sided scanning for best 'in class' scanning performance
- Renowned Magellan brand quality and reliability
- All-Weighs Scale Platter with integrated Produce Lift Bar or Produce Rail™ (Optional)
- Flash memory for easy software upgrades in the field
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Optional Value Added Features:
  - Host Download
  - Diagnostic Reporting
  - Productivity Index Reporting™
  - Cashier Training™/ Ergonomic Index - Identifies Poor Scanning Habits
- Compatible with Mettler, Bizerba and other adaptive scales
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

## LOSS PREVENTION

### All-Weighs™ Scale Platter

- The All-Weighs scale platter design provides an alternative weighing surface on top of the bonnet, allowing the user to lay produce that is too long to fit on the platter

### Checkpoint Systems and Sensormatic EAS compatible (Optional)

- Software integrates seamlessly for improved item security

## DECODING CAPABILITY

1D / LINEAR CODES	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
STACKED CODES	GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

## ELECTRICAL

AC POWER REQUIREMENTS	AC Input: 100-250 VAC, 50-60 Hz Power Consumption: Operating (Maximum): 8 Watts Operating (Nominal): 7 Watts Sleep Mode: 4 Watts
-----------------------	--

## ENVIRONMENTAL

ESD PROTECTION (AIR DISCHARGE)	25 kV
HUMIDITY (NON-CONDENSING)	5 - 95%
TEMPERATURE	Operating: 10 to 40 °C / 50 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

## INTERFACES

INTERFACES	IBM 46xx; Keyboard Wedge: Scanner Only; OEM (IBM) USB; RS-232 USB: Scanner Only
AUXILIARY PORTS	EAS Port: Powered RS-232; Remote Scale Display; Scale Host

## OPTIONAL FEATURES

ALL-WEIGHS SCALE PLATTER EAS FEATURES	Integrated Produce Lift Bar; Produce Rail™ Checkpoint Systems; Integrated EAS hardware will work with Counterpoint IX and Evolve D11 models;
VALUE ADDED FEATURES	Sensormatic: Good Read Acknowledgement Cashier Training™; Diagnostic Reporting; Host Download; Productivity Index Reporting™ (PIR)

## PHYSICAL CHARACTERISTICS

DIMENSIONS	Depth (Below Counter): 10.2 cm / 4.0 in Height (Above Counter): 13.0 cm / 5.1 in Length: Model 8401 (Short, Scanner Only): 35.6 cm / 14.0 in Model 8402 (Medium, Scanner Only): 40.1 cm / 15.8 in Model 8403 (Long, Scanner Only): 50.8 cm / 20.0 in Model 8404 (Medium, Scanner/Scale): 40.1 cm / 15.8 in Model 8405 (Long, Scanner/Scale): 50.8 cm / 20.0 in Width: 29.2 cm / 11.5 in
SCALE CAPACITIES	Adjustments Required: Calibration Only Capacity: 15.0 kg / 30.0 lb Maximum Static Weight: 68.0 kg / 150.0 lb Minimum Increment: 0.005 kg / 0.010 lb Vibration Immunity: 4 Programmable Filter Settings

## READING PERFORMANCE

MOTOR SPEED	6,000 rpm
READ HEIGHT	15.2 cm / 6.0 in
READ RATE (MAXIMUM)	5,200 lines/sec.
READING INDICATORS	Beeper (Adjustable Tone and Volume); Good Read LED
SCAN LINES	52
SCAN ZONE	360°
SIDES READ	5 Sides

## SAFETY & REGULATORY

AGENCY APPROVALS	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
ENVIRONMENTAL COMPLIANCE	Complies to EU RoHS
LASER CLASSIFICATION	Caution Laser Radiation - Do not stare into beam; CDRH Class IIa; EN 60825 Class 1; IEC 60825 Class 1

## UTILITIES

OPOS / JAVAPOS	JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at no charge.
----------------	---

## WARRANTY

WARRANTY	1-Year Factory Warranty
----------	-------------------------



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

