

Dolphin 99EXni

Mobile Computer

Dolphin® 99EXni mobile computers are certified equipment for use in potentially explosive atmospheres including chemical, oil and gas, life sciences and utilities. Moreover, the 99EXni provides user-friendly ergonomics, cutting-edge wireless technology, multi-functional data capture and extreme durability.

The reliable and intuitive Dolphin 99EXni delivers an outstanding feature set that enables improved productivity for mobile workers. Integrated Shift-PLUS™ technology provides all day battery life, minimizing the time and expense incurred when batteries need to be charged or replaced. The Dolphin 99EXni is IP67-rated and can withstand multiple 6 feet (1.8 meters) drops to concrete, ensuring years of trouble-free operation.

The 99EXni features the latest in wireless technology, including a software-definable radio that allows on-the-fly switching between GSM and CDMA networks, leading to improved network coverage and lower costs related to device provisioning and deployment. Additionally, built-in Wi-Fi provides workers with access to critical data using the new, lightning fast 802.11n standard while still supporting legacy a/b/g protocols.

Integrated motion, light and proximity sensors help conserve battery life and improve ease of use by automatically optimizing the offering for the current environment. Similarly, multiple keypad options are available to ensure that the device is configured to meet diverse data input needs. With additional features such as an ultra-bright 3.7 inch display that can be read, even in direct sunlight, the Dolphin 99EXni offers superior usability.

Extremely reliable, well designed, and full-featured, the Dolphin 99EXni is the right choice for use in hazardous locations where real-time information processing and solution reliability is critical to a company's operation.



Features

- Superior Durability: Incorporates an IP67-rated design that withstands multiple 6 feet drops to concrete and 2,000 1 meter tumbles, resulting in a lower total cost of ownership for enterprises
- Shift-PLUS Power Management: Enhances productivity by providing full shift battery life, eliminating the need for employees to carry spare batteries or chargers
- Adaptus® Imaging Technology 6.0: Enables multifunctional data capture by providing fast scanning of linear and 2D bar codes with excellent motion tolerance, as well as seamless image capture through use of an integrated color camera
- Designed For Use in Hazardous Locations:
 Certified for use in specified hazardous locations Class I and II, Division 2, ATEX Zone 2 Gas, Zone 22 Dust by Intertek

- Fast and Reliable Wireless Connectivity: Delivers full wireless coverage for applications inside and outside of the four walls, allowing real-time access to critical data
- Optimal Combination of Performance and Usability: Improves ease of use and worker efficiency with a large outdoor-viewable screen, multiple keypad options, a super fast CPU and smart sensors
- Optional Remote MasterMind® Software Package: Extends mobile workforce capabilities and reduces total cost of ownership by providing a turnkey remote device management solution
- Optional Service Made Simple™ Service Plans: Offers comprehensive, hassle-free protection on the device investment for up to five years after purchase

Dolphin 99EXni Technical Specifications

Dimensions	8.5" L x 2.7" W (keypad) x 1.5" (standard battery)/1.8" (extended battery)
	215 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery)
Weight	Standard battery – 505g (17.8 oz); Extended battery – 581g (20.5 oz)
Operating Temperature	-4° to 122°F (-20° to 50°C)
Storage Temperature	-13° to 158°F (-25° to 70°C)
lumidity	95% humidity, non-condensing
Prop	Withstands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range
umble	Exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification
nvironmental Sealing	Independently certified to meet IP67 standards for moisture and particle resistance
Hazardous Location	Class I, Division 2, Groups A, B, C, D, (Class I Div 2 US and Canada) Class II, Division 2, Groups F, G (Class II Div 2 US and Canada) Ex II 3 G D Ex ic IIC T6 Gc Ex ic IIIB T88°C Dc
ESD	Air: ±15 KV; Contact: ±8 KV
ystem Architecture	
Processor	Texas Instruments® OMAP3715 1.0GHz processor
Operating System	Microsoft® Windows Embedded Handheld 6.5 Professional and Classic
Memory	1GB discrete NAND flash x 256 MB RAM
Display	Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
Touch Panel	Industrial touch panel with resistive touch and support for finger touch and stylus
	Backlit 55-key alphanumeric, 43-key alpha shifted numeric, 34-key numeric shifted alpha (phone or calculator style)
Keypad	
Audio	Speaker, HAC compliant receiver, microphone
Camera	3.1 megapixel camera with Automated Camera Control (ACC). Features include automated picture profiles, camer Application Programming Interface (API), cooperational use of camera and imager, and flashlight utility
/O Ports	RS-232/USB 2.0/audio out/charging connector, integrated IrDA port with support for SIR mode
Storage Expansion	MicroSD card (support for up to 32GB)
3attery	Standard – Li-ion, 3.7V, 3060mAh; Extended – Li-ion, 3.7V, 5000mAh
Battery Life	Standard/Extended: 9 hours/15.5 hours (scanning and sending data over WLAN every 9 seconds) Standard/Extended: 8 hours/14.75 hours (scanning and sending data over WWAN every 15 seconds, GPS continuously receiving information)
mager/Scanner	N5600/5603 Standard range (SR), Extended range (ER), and High Density (HD) imagers with high-visibility laser or green LED aimer. All imagers have 25° angle and come equipped with Adaptus 6.0 Imaging Technology
Decode Capabilities	Reads standard 1D and 2D symbologies
Development Environment	Honeywell SDK for Windows® Embedded
Warranty	1 year factory warranty
Service Plans	Optional three-and five-year Service Made Simple programs offer worry-free mobile computing
/ireless Connectivity	
WWAN	GSM (Voice and Data): 3.9G - HSPA+ (800/850/1900/1700/2100 MHz), GSM/GPRS/EDGE (850/900/1800/1900 MH Software definable Gobi 3000 (data only): 3.9G - HSPA+/UMTS (800/850/900/1700/1900/2100MHz), GSM/GPRS/EDGE (850/900/1800/1900MHz), EVDO Rev A - 1xRTT/EVDO (800/1900 MHz); support for dual SIM card
VLAN	802.11a/b/g/n, Wi-Fi™ - certified
WLAN Security	WPA, WPA2 (Personal and Enterprise), 802.11x, EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, WMM, CWG-RF Profile, CCX v.4, WAPI

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies

















www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com







www.L-TronDirect.com 800-830-9523 info@L-Tron.com

