Compact Multifunction POS Printer with MICR

EPSON TM-U675 Printer



- High-speed MICR reading and check printing
- Quietest printer in its class
- Easy drop-in paper loading and one touch removal
- Wider throat for smooth drop-in validation
- Superior slip handling with built-in forms stopper
- Optimized features and small footprint perfect for busy counters

This easy-to-use POS printer sports superior slip handling and printing speeds that satisfy the most demanding customer requirements.

If counter space is at a premium but you're not willing to sacrifice performance and flexibility, the feature packed TM-U675 will satisfy your requirements for years to come. The accurate MICR reader bundled with fast check handling and printing speed is a perfect match for the retail and banking environment.

Multifunction

Boasting some of the fastest printing speeds in its class, coupled with the versatile paper handling, the TM-U675 will help you complete customer transactions in less time.

User-friendly design

The TM-U675 comes packed with features to streamline operation and reduce training time. To improve the handling of documents such as coupons, gift certificates and void slips, the TM-U675 supports 90 degree print rotation and includes a mechanical forms stopper for extra document stability.

A wider throat design enables quick and smooth drop-in validation. And paper handling and drop-in loading make using the TM-U675 a pleasure. Add to this an ASB (Automatic Status Back) function to keep operators constantly informed of printer status and built-in maintenance counters for implementing scheduled routine maintenance.

Reliability and flexibility

Designed to withstand the rigors of high transaction environments, the TM-U675 is built with the highest quality engineering and most rugged design of any printer in its class. And, only EPSON can protect your hardware investment for years to come. By utilizing our unique Connect-It[™] interface modules, customers can be assured that their printers won't be obsolete the moment their POS systems are replaced.

Increased value and customer satisfaction

EPSON's new high-quality multifunction printer includes more optimized features than any printer in its class. The TM-U675 prints slips, receipts, and validates in a single compact unit, bringing top productivity in a minimum of counter space. And, with the lowest acoustic noise of any comparable printer, the TM-U675 offers quiet, efficient operation providing quicker transactions and increased customer satisfaction.

> EPSON[®] EXCEED YOUR VISION

EPSON TM-U675 Printer

| TM-U675 Specifications | |
|------------------------|--|
| Print Method | 9-pin, serial impact dot matrix |
| Print Font | 5 × 9 / 7 × 9 |
| Column capacity | Receipt: 37 / 50 columns, Slip / Validation: 45 / 60 columns |
| Character size | 1.56 × 3.1 mm (W × H) / 1.24 × 3.1 mm (W × H) {0.061 × 0.122" / 0.049 × 0.122"} |
| Character set | 95 Alphanumeric, 37 International, 128 × 11 Graphic characters |
| Print Speed | Approx. 5.14 lps (40 columns, 17.8 cpi) |
| Paper Dimensions | Receipt or Journal: 82.5 ± 0.5 × diameter 83 mm {3.25 ± 0.02 × diameter 3.27"} Slip: 70 to 148 × 150 to 210 mm (W × L) {2.76 to 5.83 × 5.91 to 8.27"} Validation: 148 to 150 × 70 to 210 mm (W × L) {5.83 to 5.91 × 2.76 to 8.27"} |
| Paper Thickness | Receipts or Journal: 0.06 to 0.085 mm / sheet {0.0024 to 0.0033"} (Total thickness: 0.2 mm {0.0079"} or less) Slip: 0.09 to 0.2 mm / sheet {0.0035 to 0.0079"} (Total thickness: 0.09 to 0.31 mm {0.0035 to 0.0122"}) |
| Validation | 8 lines |
| Copy Capability | One original and two copies |
| Inked Ribbon | ERC-32 |
| Ribbon Life | 4,500,000 characters |
| Power Supply Voltage | 24 VDC ± 10% |
| Current Consumption | Approx. 1.7 A (mean) |
| D. K. D. Function | 2 drivers |
| Reliability | MTBF 180,000 hours MCBF 37,000,000 lines |
| Overall Dimensions | 186 × 298 × 195 mm (W × D × H) {7.3 × 11.7 × 7.7"} |
| Mass | Approx. 4.8 kg {10.6 lb} With autocutter approx. 5.8 kg {12.8 lb} |
| EMI Standards | VCCI class A, FCC class A, CE marking |
| Safety Standards | UL, CSA |
| Interfaces | RS-232C / Bi-directional parallel / RS-485 / USB / Connect-It™* |
| Factory Options | Autocutter, MICR |
| Data Buffer | 4 KB or 45 bytes |
| NV Bit Image Memory | 384 KB can be used to store graphic files |

Inch values are approximate.

cpi: characters per 25.4 mm (characters per inch)

lps: lines per second

* To find out more about our line of Connect-It Interfaces talk to your EPSON Sales Representative.



Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • (562) 290-5304 • http://pos.epson.com ©2012 Epson America, Inc. Epson and ESC/POS are registered trademarks of Seiko Epson Corporation. Connect-It is a trademark of Epson America, Inc. All other trademarks are the property of their respective owners. Epson is a member of the OPOS committee. Specifications are subject to change without notice.





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

Get in touch with us on social media!

www.L-Tron.com