Epson TM-L90-i Series

DATASHEET





The Epson TM-T88V-i provides users with a straightforward and elegant printing solution, with no need for drivers. Ideal for use with tablet PCs or mobile phones, the TM-T88V-i is simple to use and maintain, with the ability to print from any device running an HTML 5 compatible web browser. In addition, the TM-T88V-i has greyscale printing for the addition of logos and images to receipts.

Ease of use

The Epson TM-T88V-i provides convenient and straightforward receipt printing directly from tablet PCs and other mobile devices without the need for drivers, so a LAN or WLAN connection is all that you will need. In fact, the TM-T88V-i can print from any device that is running a popular web browser.

Intelligent functionality

Using a unique built-in intelligence called ePOS-Print, the TM-T88V-i is able to receive XML commands from web applications in addition to communicating directly with browsers supporting HTML 5, such as Safari®, Chrome™, Internet Explorer® and the standard Android browser. This makes the TM-T88V-i ideal for restaurants, hotels and bars using tablet PCs or mobile phones for ordering. Additionally, users can switch between applications without changing printer settings, and configure the printer from mobile devices.

Control connected devices

Due to ePOS-Print's ability to recognise all major ESC/POS functions which are sent as XML commands, the TM-T88V-i can control cash drawers, as well as additional printers with a wired or wireless UIB interface, such as order-driving kitchen printers.

Reliable, easy servicing and maintenance

The TM-T88V-i is ideal for businesses that require a stable system that is costeffective to implement and maintain. With no drivers to update and no need for a permanent connection to a PC or server, servicing and trouble-shooting are simple. In addition, fewer pieces of equipment mean less power consumption, reducing bills and environmental impact.

KEY FEATURES

- Print directly from HTML 5 browsers
- No drivers to install or update
- Responds to web application commands
- Recognises functions sent as XML
- Add logos and images to materials



PRODUCT SPECIFICATIONS

FONTS & STYLES	
Column capacity	Paper width 80 mm, 56 / 42
PAPER	
Paper size	79.50 ± 0.50 (W) mm x dia 90.00 mm,
	69.50 ± 0.50 (W) mm x dia 90.00 mm,
	37.50 ± 0.50 (W) mm x dia 90.00 mm
FONTS & STYLES	
Print Speed	150 mm/sec
Printing Font	ANK
Column capacity receipt	Paper width 80 mm, 56 / 42
Character size	0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density	180 dpi x 180 dpi
INTERFACES	
Interfaces	USB 2.0 Type A (4x), Ethernet interface (100 Base-TX / 10 Base-T), USB 2.0 Micro-AB
DATA BUFFER	
Data Buffer	4 kB or 45 Bytes
GENERAL	
Product dimensions	145 x 195 x 148 (Width x Depth x Height)
Product weight	1.6 kg
Sound Pressure	Operation: 55 dB (A)
Color	Epson Cool White
Installation	Epson Cool White horizontally
Installation Humidity	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90%
Installation	Epson Cool White horizontally
Installation Humidity	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C
Installation Humidity Temperature	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C
Installation Humidity Temperature STANDARDS COMPLIANC	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C
Installation Humidity Temperature STANDARDS COMPLIANC EMC Standards	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C
Installation Humidity Temperature STANDARDS COMPLIANC EMC Standards Safety standards	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C
Installation Humidity Temperature STANDARDS COMPLIANC EMC Standards Safety standards OTHER FEATURES	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C
Installation Humidity Temperature STANDARDS COMPLIANC EMC Standards Safety standards OTHER FEATURES Cutter	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C E CE marking TÜV Partial Cut
Installation Humidity Temperature STANDARDS COMPLIANC EMC Standards Safety standards OTHER FEATURES Cutter Factory options	Epson Cool White horizontally Operation 10% - 90%, Storage 10% - 90% Operation 5° C - 45° C, Storage -10° C - 50° C CE marking TÜV Partial Cut Autocutter, Near-end sensor

Epson TM-L90-i Series

WHAT'S IN THE BOX

AC Adaptor

SUPPLIES

- 3yrs on-site swap
- Epson OT-WL01 (732): Wireless LAN set for Epson TM-i C32C890732
- Epson OT-WL01 (732A0): Wireless LAN set for Epson TM-i
- 3yrs on-site swap

OPTIONAL ACCESSORIES

 Epson OT-WL01 (732): Wireless LAN set for Epson TM-i C32C890732



For more information please contact:

Telephone:	0871 222 6702 (UK)+ 01 436 7742 (Republic of Ireland)
E-mail:	enquiries@epson.co.uk
Chat:	etalk.epson-europe.com
Fax:	0871 222 6740

Web: www.epson.co.uk www.epson.ie



+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

Get in touch with us on social media!

www.L-Tron.com