Epson® Mobilink® P60II Wireless Printer



- Industry-leading operational battery life up to 46 hours*
- 4-foot drop rating and IP54 environmental certified
- Highest printing speed in its class
- Supports 802.11b/g/n with 2.4GHz/5GHz compatibility and Bluetooth® 2.1 + EDR
- Long-lasting autocutter
- Paper-saving options
- Print width up to 54mm on standard 58mm media
- Zebra[®] emulation available

The Mobilink P60II wireless printer is the latest addition to Epson's family of mobile printers. Faster, lighter and more secure than ever before, it is ideal for mobile printing applications for retail and food service.

Great features for mobile printing

The Mobilink P60II has all the features you need to print anywhere, anytime. Compact and light weight, it offers the fastest printing in its class with speeds up to 100mm/second, an industry-leading battery life, flexible connectivity, a ruggedized design to ensure reliability in even the harshest environments and more.

Best-in-class battery life

To ensure uninterrupted service to your customers, Epson's Mobilink P60II features an industry-leading operational battery life of up to 14 hours with 802.11 models and up to 46 hours with Bluetooth models*.

Reduce your paper costs

The Mobilink P60II is the only wireless printer that comes with paper-saving options that can reduce your paper usage by up to 23%. The paper-saving settings are easy to use without changing your application and do not affect print quality, readability and font size.

Your choice of connectivity

Epson's Mobilink P60II is available with 802.11b/g/n with 2.4GHz and 5GHz or Bluetooth® 2.1 + EDR for fast and easy integration. And it supports all the leading mobile operating systems including iOS, Android and Windows with 802.11 and Android and Windows with Bluetooth.

Compatible and ready to go

Epson's Mobilink P60II wireless printer is compatible with today's best-of-breed and component-based POS systems and the latest industry-standard wireless security protocols. The printer comes complete with ESC/POS®, OPOS, JavaPOS and Windows® drivers which means your current applications are instantly compatible. And Zebra emulation is also available.

Backed by the leader

The Mobilink P60II features the quality and reliability that Epson is known for, a low total cost of ownership and is backed by our leading service and support programs.



All the features you need

- Industry-leading operational battery life up to 46 hours*
- 4-foot drop rating and IP54 environmental certified
- Highest printing speed in its class
- Supports 802.11b/g/n with 2.4GHz/5GHz compatibility and Bluetooth® 2.1 + EDR
- Long-lasting autocutter
- Paper-saving options
- Print width up to 54mm on standard 58mm media •
- Zebra® emulation available

Printer

Print method	Thermal line printing
Print speed (max.)	Receipt mode 100mm/sec, label mode 80mm/sec; peeler mode 40mm/sec
Dot/line	420/432 dots
Print font	
Font	Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16
Column capacity	58mm paper, Font A/B/C, 35/42/52 columns; 60mm paper, Font A/B/C, 36/43/54 columns
Character size	1.5 × 3.0 / 1.25 × 3.0 / 1.0 × 2.0 mm (W × H)
Character set	95 Alphanumeric, 48 International, 128 x 10 Graphic
Barcode	1D: EAN-8, EAN-13, UPC-A, UPC-E, JAN13, JAN8, Code 39, Code 93, Code 128, ITF, CODEBAR, GS-1- 128, GS1 DataBar, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded
	2D: QR Code, Maxi Code, PDF417, Composite, Data Matrix, RSS/GS1 and Aztec
Characters per inch	17/20/25 срі
Paper width	Paper or labels, 58mm or 60mm width (receipt version) Paper or labels, 30–60mm (label version)
Paper diameter (max.)	51mm
Reliability	10 million printing lines; 500,000 autocutter (receipt version)

General information

Interface	802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 2.1 + EDR
Supported mobile operating systems	WiFi (802.11): iOS, Android and Windows Bluetooth: Android and Windows
Data buffer	4096 bytes
Autocutter	Partial cut, left uncut (receipt version)
Peeler	Automatic label removal from backing (label version)
Audible alert	Programmable buzzer
Sensors	Paper out (receipt and label versions) Gap, black mark, label taken (label version)
LED indicators	
Green LED	Power (ON=Power on, OFF=Power off)
Orange LED	Only shown when power is ON Error, Paper end, Cover open, Battery level low (printer does not operate)
Blue LEDs	Four battery level indicators: 3 LED ON = approx. 100%–60% 2 LED ON = approx. 60%–20% 1 LED ON = approx. 20%–10% 1 LED Flashing = approx. 10%–1%
Software	TM-P60II Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P60II Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page
Power	Custom Lithium-Ion battery pack, AC adapter (option)
Charging	AC adapter (2.5 hours to full charge), custom quad bay charger (2.5 hours to full charge)
Battery life	Up to 14 hours with 802.11n, up to 46 hours with Bluetooth 2.1 + EDR*

*The Mobilink P60II battery life can last up to 14 hours for WiFi and up to 46 hours for Bluetooth. Battery life can vary significantly depending on usage.



SD-DSMBLKII-A

ISO 9001 Registered USB **RoHS** UnifiedPOS JAVAPOS[™]

Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • (562) 290-5304 ©2013 Epson America, Inc. Epson is a registered trademark and Epson Exceed Your Vision is a registered logo-mark of Seiko Epson Corporation. Mobilink is a trademark of Epson America, Inc. All other trademarks are the property of their respective owners. Specifications are subject to change without notice.

Operating temperature Drop rating	0° C to 45° C 4 feet
Overall dimensions	4.05" x 6.25" x 2.55" (103 x 159 x 65 mm) (W x D x H)
Weight	Receipt version 1.4 lbs (630g) with battery, belt clip Label version 1.3 lbs (600g) with battery, belt clip
Color	Epson Black (EBCK)
Warranty	One-year limited warranty and optional two-year warranty

What's in the box

Mobilink P60II Battery (Model: OT-BY60II) Roll paper (for checking initial movement of the printer) User's manual USB cable saddle (for secure cable connection) USB cable Belt clip (already attached to printer) 58mm spacer (already attached to printer)



Accessories

Battery (OT-BY60II) Quad Charger (OT-CH60II) Power Supply (PS-11) Carry Strap (OT-ST60) Padded Case (SOFTSTELL V1)





Spare Battery







AC/DC Power Supply

Carry Strap

Padded Case





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

Get in touch with us on social media!

www.L-Tron.com