

# CognitiveTPG

## C Series Compact Industrial Thermal Label Printer

Big box performance in a desktop footprint and price, with unbeatable reliability



“One printer for your entire enterprise”

A compact label printer ideal for applications that require an efficient use of space, yet with the capacity to perform like industrial sized barcode label printers! C Series printers can be used throughout your entire enterprise.

The C Series represents CognitiveTPG's most versatile line of thermal label printers. Its small desktop size holds the performance associated with big box printers. The C Series printers deliver value and functionality to fit multiple applications and industries, from warehouse floor to the pristine pharmacy environment.

- Rugged and reliable all-metal printer mechanism for high volume printing applications
- Die-cast metal user interface to withstand harsh environments
- Menu-driven LCD controls for easy set-up without a computer
- Full connectivity suite, including internal Ethernet, USB ports and serial or parallel communication ports
- Fast print speeds up to 8 ips
- Real-time clock (RTC) for date- and time-sensitive applications
- 8" OD roll capacity for continuous printing



C Series-- A perfect standalone application



# C Series Compact Industrial Thermal Label Printer

## PRODUCT HIGHLIGHTS

### Metal vs. Plastic

One touch tells you that this is not a plastic printer. We know the environment and the workload the C Series printers must endure. Using solid metal framing, print mechanism, and components gives it the rugged and industrial strength to stand up to some of the most challenging environments. This industrial build is what enables the C Series to compete with table top printers.

### Flexibility provides versatility

The C Series delivers flexibility and versatility to meet mostly any applications. For on-demand printing applications, the C Series small footprint, LCD menu, and USB-A port provides a user friendly solution. With high volume printing, the back expands to accommodate an 8 inch roll to maintain its compact footprint. The C Series also offers a 300 dpi print solution for high resolution and graphics printing.



## TECHNICAL SPECIFICATIONS

	2 inch Model	4 inch Model
<b>PRINT</b>		
Method	Direct Thermal or Thermal Transfer	Direct Thermal or Thermal Transfer
Width (max)	2.118" (53.8 mm)	4.094" (104 mm)
Length (max)	322" (8179 mm)	322" (8179 mm) at 203 dpi
Speed (max)	8 ips (203.2 mm/sec) w/LCD display	8 ips (203.2 mm/sec) w/LCD display
Resolution	203 dpi (8 dpmm). Optional 300 dpi (12 dpmm)	203 dpi (8 dpmm). Optional 300 dpi (12 dpmm)
<b>MEDIA</b>		
Width	0.75 - 2.84" (10 mm - 72 mm)	2" - 4.63" (50 mm - 119 mm)
Roll Diameter	8" (203 mm)	8" (203 mm)
Ribbon Length (TT only)	6500" (165 mm)	5500" (140 mm)
Indexing	Continuous, gap, black bar, black mark, notch/hole	
Media Caliper	Up to .01" (.254 mm)	Up to .01" (.254 mm)
<b>BARCODES</b>		
Add2, Add5, Codabar, Code39, Code93, Code 128A/B/C, D2of5, I2of5, S2of5, EAN8, EAN13, EAN128, MSI/11, Plessey, Postnet, UPCA/A+/E/E1		
<b>FONTS</b>		
Bitmapped	7 styles with up to 10x10 magnification, variable boldness and spacing	
International	Sans serif font in 7 pt. sizes, up to 4x4 magnification, variable boldness and spacing	
Scalable Smooth Fonts	3 Ultra Font styles for smooth characters in any size and boldness	
Rotations	0, 90, 180, 270 degrees	
Optional	Kanji, Korean, and OCR fonts available	
<b>GRAPHICS</b>		
PCX and BMP formats		
<b>MEMORY</b>		
RAM - 16 MB, Flash - 8 MB		
<b>COMMUNICATIONS</b>		
USB-A/B, Serial or Parallel, Ethernet (internal)		
<b>REAL-TIME CLOCK (RTC)</b>		
Standard, All Models		
<b>ELECTRICAL</b>		
Auto-ranging 100-240VAC, 50-60 Hz, 24VDC output		
<b>ENVIRONMENTAL</b>		
Operates at 41°F to 104°F (5°C to 40°C)		
<b>PHYSICAL CHARACTERISTICS</b>		
Width	5" (127 mm)	6.9" (175 mm)
Height	7.1" (181 mm)	7.1" (181 mm)
Depth	10.04" (255 mm)	10.04" (255 mm)
Weight (DT/TT)	5.02 lbs. (2.28 kg) / 5.23 lbs. (2.38 kg)	5.91 lbs. (2.69 kg) / 6.10 lbs. (2.77 kg)
<b>ACCESSORIES</b>		
Start-up guide, power supply, Window's driver, programmer's guide, NiceLabel design software, 8" OD media roll adapter, USB cable. Optional communication cables		
<b>WARRANTY</b>		
Printer	24 months from date of purchase (requires registration and excludes printhead)	
<b>PROGRAMMING LANGUAGE</b>		
Cognitive Programming Language (CPL), EcPL and ZcPL language emulation. Optional laser printer emulation (PCL5)		



Meets strict European standards, such as RoHS & WEEE compliance for non-toxicity of components and recyclability.

**COGNITIVE TPG**  
Innovation built to last

CognitiveTPG, LLC  
950 Danby Road, Suite 200, Ithaca, NY 14850  
Toll Free: 800.732.8950 Phone: 607.274.2500 Fax: 607.274.2449  
www.CognitiveTPG.com  
Copyright 2014 CognitiveTPG. All Rights Reserved.

280-0007-01-0114 Rev B



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

