

## Product profile



# Duratran II™ Kimdura Label

Thermal Transfer Film



- Recommended for outdoor applications
- Resistant to grease and oil
- Tear resistant
- Available with permanent or removable adhesive
- Excellent print quality for graphics and high resolution barcodes

Intermec's Duratran II Kimdura label offers excellent performance in a wide range of challenging tracking applications. This durable label readily endures outdoor exposure to rain, snow, and ultraviolet light for one year or more. With its synthetic facesheet, it is perfect for challenging environments where it will encounter exposure to moisture, oils, and grease. This label stock is ideally suited for labeling applications such as:

- Industrial bins
- Automotive components
- Medical devices
- Medical specimens (exposure to moisture or some chemicals)
- Outdoor furniture
- Horticultural products
- Building products
- Farming equipment
- Oil and gas industries
- Drum labels

### Better Together

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance.
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting.
- When Intermec media is used exclusively with Intermec printers, the Free Printhead Replacement Program offers significant cost savings.

**Product Characteristics****Face Stock**

**Description:** Smudgeproof Kimdura Label

**Physical Attributes:** Caliper (Mils) 3.9 - 4.5

**Adhesive**

**Description:** Acrylic Permanent

**Physical Attributes:** Caliper (Mils) 0.5 - 0.8

**Performance Attributes:** Peel Adhesion (oz/in 90° Stainless Steel) 32.5 Target

**Liner**

**Description:** 54# Bleached Kraft

**Physical Attributes:** Caliper (Mils) 3.1 - 3.4

**Ribbon Compatability**

TMX 1000

TMX 2000

**Recommended for Outdoor Use:** +One Year

**Compliance**

FDA

**Environment**

**Storage Temperature:** 40°F to 80°F

**Storage Humidity:** 35% to 75%

**Shelf Life:** 12 months

**Minimum Application Temperature:** 45°

**Service Temperature:** -40°F to 250°F

**North America****Corporate Headquarters**

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

**North Latin America****Headquarters Office**

Mexico  
Phone: +52 55 52-41-48-00  
Fax: +52 55 52-11-81-21

**South Latin America****Headquarters Office**

Brazil  
Phone: +55 11 3711-6776  
Fax: +55 11 5502-6780

**Europe/Middle East & Africa Headquarters Office**

Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

**Asia Pacific****Headquarters Office**

Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

**Internet**

[www.intermec.com](http://www.intermec.com)  
Worldwide Locations:  
[www.intermec.com/locations](http://www.intermec.com/locations)

**Sales**

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW:  
00 800 4488 8844  
Toll ROW: +44 134 435 0296

**OEM Sales**

Phone: (425) 348-2762

**Media Sales**

Phone: (513) 874-5882

**Customer Service and Support**

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

Copyright © 2011 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 612126-01B 05/11

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

