

Duratran II Paper Label

Thermal Transfer Paper



- Duratran II labels provide high-quality, cost-effective printing for general use applications
- Compatible with TMX1500 and TMX2200 ribbons
- Offered with a variety of adhesive options
- Take From Stock labels available in an assortment of colors

Duratran II Paper Label

Intermec's Duratran II paper label is a coated, thermal transfer paper label that exhibits excellent print quality when paired with the TMX1500 and TMX2200 ribbons. Duratran II paper labels are offered with a variety of adhesive options and are recommended when moderate abrasion, heat, or sunlight is present. Stock Duratran II products offer a robust general-purpose permanent adhesive that is excellent for use on corrugated containers, plastics, and many other common substrates. Special adhesives are available with custom orders. This label stock is ideally suited for applications such as:

- Shipping label
- Inventory tracking label
- Work-in-process
- Receiving label
- Bin labeling
- General purpose labeling

Better Together

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting
- When Intermec media is used exclusively with Intermec printers, the Free Printhead Replacement Program offers significant cost savings

Product Characteristics:

Face Stock

Description: Coated Paper Label
Physical Attributes: 2.6 - 3.2 mils

Adhesive

Description: Acrylic Permanent
Caliper: 0.4 - 0.6 mil
Peel Adhesion (90° Stainless Steel): 33.0 target

Liner

Description: 42# white kraft
Physical Attributes: 2.3 - 2.8 mils

Ribbon Compatibility

TMX1500
TMX2200

Outdoor Use: Not recommended for outdoor use

Environment

Storage Temperature: 40°F to 80°F
Storage Humidity: 35% to 70%
Shelf Life: 12 months
Minimum Application Temperature: 25°F
Service Temperature: -65°F to 200°F

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

Intermec Deutschland

Burgunder Strasse 31
40549 Düsseldorf
Germany
Phone: 0049 211 53601-0
Fax: 0049 211 53601-50
Email: germany.marketing@intermec.com
Web: www.intermec.de

South America & Mexico

Headquarters Office
Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East & Africa

Headquarters Office
Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611841-A 09/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

