



B-Series Model B2 Rev. B Fan-less All-in-One Touchcomputers

The **Elo Touch Solutions B-Series Fan-less B2 model** provides a compact, configurable, ruggedized touchcomputer in two screen sizes: 15-inch and 17-inch. These models are available with a choice of industry-leading Elo touch technologies: AccuTouch ("no-bezel" resistive) or iTouch Plus (zero-bezel multi-touch surface acoustic wave). The B-Series B2 models are fan-less—well-suited for environments where noise may be an issue—and can meet the diverse needs of a wide variety of point-of-sale (POS), point-of-information (POI), and point-of-service venues, including retail and hospitality display units, customer loyalty systems, internet access sites and mobile kiosks.

The B-Series touchcomputers have a compact, stylish design, with a choice of configuration and customer-installable peripheral options as well as ease of serviceability. These models feature a fan-less Intel Atom™ Dual-Core 1.86GHz N2800 processor, and support multiple customer-installable memory and storage configurations. For applications requiring even higher performance, look at the powerful, fan-cooled B3 models with the 3rd Generation Intel Core-i3, 3.3GHz i3-3220 processor with HD2500 graphics.

Features

- Small footprint, retail-hardened, flexible touchcomputer
- Fan-less model ideal for quiet environments
- Full range of standard connectivity ports for retail POS/POI and hospitality applications
- Customer-installable peripheral, memory and storage options
- Choice of industry-leading Elo touch technologies: AccuTouch ("no-bezel" resistive) and iTouch Plus (zero-bezel multi-touch surface acoustic wave)
- "Designed for touch" from the ground-up; stable stand and tiltable display
- 3 year standard warranty plus Elo quality and reliability

Benefits

- Outstanding configurability and customization options to meet all your connectivity needs
- Zero-bezel models provide a seamless, edge-to-edge design for a sleek appearance that is easy to clean and maintain
- Stability to withstand the rigors of use in a public environment



B-Series Model B2 Rev. B Fan-less All-in-One Touchcomputers

Computer Specifications

15B2 15-inch model:

17B2 17-inch model:

Enclosure Color	Dark grey	
Processor	Intel 1.86GHz Atom Dual-Core N2800; 1MB L2 Cache; 2.5 GT/s Direct Media Interface (DMI)	
Memory (RAM)	2GB 1333MHz DDR3 SO-DIMM on 1 of 2 slots. Expandable to 4GB	
Chipset	Intel NM10 Express	
Video	Intel GMA 3600	
Serial Ports	2 x Native RS-232	
USB Ports	6 x USB 2.0 (4 on I/O, 1 x USB side access, 1 x USB hidden/protected). (Additional internal ports available for optional Elo peripherals.)	
Ethernet Port	1 x LAN RJ45 (Gigabit)	
Cash Drawer Port	Built-in 12V/24V Cash Drawer Port (24V default; selectable via jumper)	
Additional Video Out	1 x 2nd VGA out port	
Audio Ports	1 x 3.5mm line-in; 1 x 3.5mm line-out; 1 x 3.5mm mic-in	
Speakers	Two 2W internal speakers	
Hard Disk Drive	320GB 2.5" 5400rpm Advanced Format (4K) SATA HDD	
Real-Time Clock	Replaceable lithium-ion battery for clock	
Operating System Options	No Operating System; Microsoft Windows XP Professional Service Pack 3 (32-bit only); Microsoft Windows 7 Professional Service Pack 1 (32-bit only)	
Touchcomputer Dimensions (max. with stand, dimensions vary with tilt and options)	14.0" x 10.5" x 14.3" (354.4mm x 267mm x 363.5mm)	15.2" x 10.5" x 14.2" (386.4mm x 267mm x 361.0mm)
Weight	With stand: 17.9lbs (8.1kg); without stand: 13.0lbs (5.9kg); shipping: 24.5lbs (11.1kg)	With stand: 19.8lbs (9.0kg); without stand: 15.0lbs (6.8kg); shipping: 26.4lbs (12.0kg)
Shipping Box Dimensions	17.4" x 10.2" x 21.9" (443mm x 258mm x 555mm)	
Power Consumption (max.)	47W (without peripherals)	48W (without peripherals)
Temperature	Operating: 32°F to 95°F (0°C to 35°C); Storage -4°F to 140°F (-20°C to 60°C)	
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%	
Warranty	3 years	
MTBF	50,000 hours demonstrated	
Cables and Accessories	North American and European power cables included	
Power Supply	External 12VDC universal-type power supply brick; AC input voltage: 100-240VAC; Input frequency: 50-60Hz; max. output power: 150W (max. draw: 170W)	
Agency Certification	UL/cUL, FCC, TUV, CE, CB, Mexico COC, Argentina S-mark (power brick only), C-Tick, VCCI, CCC	
Other Features	Serviceable internal components; removable base with 100mm VESA mounting; threaded holes on bottom of base for mounting; Kensington security lock	

Display Specifications

Display	15.0" diagonal, Active matrix TFT LCD (CCFL), 4 x 3	17.0" diagonal, Active matrix TFT LCD (LED), 5 x 4
Useful Screen Area (W x H)	12.0" x 9.0" (304.0mm x 228.0mm)	13.3" x 10.6" (338.0mm x 270.0mm)
Native (optimal) Resolution	1024 x 768	1280 x 1024
Colors	16.7 million	
Brightness (typical)	LCD panel: 250 nits; AccuTouch: 200 nits; iTouch Plus: 225 nits	
Response Time—total (typical)	8 ms	5 ms
Viewing Angle (typical)	Horizontal: ±70° or 140° total; Vertical: 60°/65° or 125° total	Horizontal: ±80° or 160° total; Vertical: ±80° or 160° total
Contrast Ratio (typical)	700:1	1000:1
Controls (bottom)	Power, brightness up, brightness down, volume up, volume down	
Security Lockouts	Power and control buttons lock	
Available Touch Technologies	AccuTouch ("no-bezel" resistive); iTouch Plus (zero-bezel multi-touch surface acoustic wave)	

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
301 Constitution Drive
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4800
Fax 1-650-361-4722
customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and iTouch are trademarks of Elo Touch Solutions, Inc. Windows is a trademark of Microsoft Corporation.
Copyright 2013 Elo Touch Solutions, Inc. All rights reserved. DS000033, rev 02/2013

www.elotouch.com





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

