

Panasonic

TOUGHPAD FZ-X1

- Android[™] Operating System
- Voice and Data Technology
- Qualcomm® Quad-core Processor
- MIL-STD-810G, 10' Drop, All-weather IP65 and IP68 Dust and Water-resistant Design
- 14-hour Hot-swappable Battery
- Optional Integrated Barcode Reader, Magstripe Reader and Certified ANSI 12.12.01 for Hazardous Locations
- Glove-enabled Multi Touch Daylightreadable Display
- 3-year Warranty with Business Class Support









THE WORLD'S MOST RUGGED 5" HANDHELD TABLET, WITH VOICE AND DATA TECHNOLOGY.

The new Panasonic Toughpad® FZ-X1 is the world's most rugged 5" handheld tablet, with optional data, voice and push-to-talk technology.* This fully-rugged tablet is MIL-STD-810G and IP65/68 tested with a 10' drop resistance, operating temperature of -4°F to 140°F and a glove-enabled multi touch daylight-readable display. The Toughpad FZ-X1 boasts the world's longest battery life for a handheld tablet, with 14 hours of continuous data access. The battery quickly charges to 50% in just one hour, and is hot-swappable. Customized options include integrated barcode reader, magstripe reader and certified ANSI 12.12.01 for hazardous locations.



1.800.662.3537 us.panasonic.com/x1



^{*}X1 telephony model available January 2015.



Panasonic

| DURABILITY | World's most rugged design |
|----------------------------------|---|
| | MIL-STD-810G (shock, vibration, rain, dust, sand, altitude, freeze/thaw, high/low temperature, |
| | temperature shock, humidity, explosive atmosphere) |
| | ■ IP65 and IP68 sealed all-weather design (submersible up to 5' for 30 minutes) |
| | 10' drop-resistant Operating temperature of -4°F to 140°F |
| | Port covers |
| | Raised bezel for LCD impact protection |
| SOFTWARE | ■ Android TM (4.2.2) |
| СРИ | Qualcomm® APQ8064T 1.7GHz Quad-core |
| STORAGE & MEMORY | ■ Memory 26B¹² |
| | Storage 32GB^{1,2} - Up to 64GB additional with optional microSDXC card³ |
| DISPLAY | |
| DISPLAT | 5" high definition 1280 x 720 daylight-viewable display 10-point capacitive gloved multi touch with glove touch mode |
| | - Rain sensing touch mode |
| | – 2-500 nit |
| | – VA display with direct bonding |
| | - Anti-reflective and anti-glare screen treatments |
| | – Automatic screen rotation |
| AUDIO | Integrated microphone x 3 |
| | Loud volume twin speakers 100 db |
| KEYBOARD & INPUT | ■ 10-point gloved multi touch + digitizer screen |
| | 2-4 tablet buttons (user-definable) |
| | On-screen QWERTY keyboard |
| SENSORS | Ambient light sensor, digital compass, gyro and acceleration sensors |
| CAMERAS | ■ HD 1.3MP webcam |
| | 8MP rear camera with LED light |
| EXPANSION | ■ microSDXC |
| INTERFACE | Docking connector |
| | ■ USB 2.0 (x 1) ⁴ 4-pin |
| | Headphone & microphone Mini-jack stereo |
| WIRELESS | ■ IEEE802.11 a/b/g/n/ac |
| | 4G LTE, HSPA+, UMTS, EDGE, GPRS, CDMA 1x, EVDO Rev.A Micro SIM card slot x 2 |
| | Bluetooth® v4.0 (class 1) |
| | ■ GPS 2m CEP50 (±2 to 4m) |
| | Near Field Communication (NFC) |
| | – Felica Type A, Type B |
| POWER SUPPLY ⁵ | Li-lon battery pack 3.8V, 6200mAh |
| | Battery operation: |
| | - Standby up to 1000 hours; Talk up to 23 hours; Barcode up to 20.5 hours |
| | Bridge battery: 30 seconds to 2 minutes |
| | Continuous use data: |
| | - 14 hours |
| | Battery charging time: |
| | Power on approx. 3 hours; Power off approx. 3 hours; 50% charge in approx. 1 hour AC adapter sold separately |
| | AC adapter sold separately |
| POWER MANAGEMENT | Consumption approx. 18W Hot-swappable battery |
| SECURITY FEATURES | |
| SECURITI FEATURES | FIPS140-2 level-1 compliant ARM® TrustZone® (Built-in) |
| WARRANTY | 3-year limited warranty, parts and labor |
| DIMENSIONS & WEIGHT ⁶ | |
| יוויום א פאטוכאווים מ WEIUfli | 6.5"(L) x 3.4"(W) x 1.2"(H) Approx. 0.94 lb. |
| | |

INTEGRATED OPTIONS7

- Optional 1D/2D barcode reader
- Optional magnetic stripe reader with hand strap and stylus
- Certified ANSI 12.12.01 for hazardous locations

ACCESSORIES

| 7100200011120 | |
|--|--------------|
| AC Adapter (60W) for Device and Desktop Cradle⁸ | CF-AA6373AM |
| (sold separately from device, included with cradle) | |
| AC Adapter (110W) for 4-Bay Cradle and 4-Bay | CF-AA5713AM |
| Battery Charger (included with both cradles) | |
| ■ Car/DC Adapter | CF-AAV1601AW |
| Desktop Cradle with Spare Battery Charging Slot | TBD |
| (60W power adapter included) | |
| 4-Bay Cradle (110W power adapter included) | FZ-VEBX121M |
| ■ A-Ray Rattery Charger | F7-VCBX111M |

(110W power adapter included)

 Hand Strap with Stylus (corner rings included) TBD FZ-VSTX111U Holster and Belt Battery Pack FZ-VZSUX100J Shoulder Strap (corner rings included) ■ Vehicle Dock TBD

Please consult your reseller or Panasonic representative before purchasing.

¹ 1GB = 1,000,000,000 bytes.

 $^{\rm 2}\,\text{Total}$ usable memory will be less depending upon actual system configuration.

¹ Operation has been tested and confirmed using Panasonic SD Memory Card with a capacity of up to 26B, Panasonic SDHC Memory Card with a capacity of up to 46B. Operation on other SD equipment is not guaranteed.

operation in unerstable despinations in the guidantieur.

A Dees not quarantee operation of all USB-compatible peripherals.

Approximate time. Battery performance features such as charge time and life span can vary according to the conditions under which the computer and battery are used. Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other customer preferences. 14 hours based on Panasonic test conditions. Talk time may change according to cellular

network condition. Measured with VOIP application.

6 Length measurements do not include protrusions. Weight varies with options.

⁷ Accessories and Integrated Options may vary depending on your configuration. Visit Panasonic website for more accessories and details.

 8 The AC adapter is compatible with power sources up to 240V AC adapter. The AC adapter is sold separately.









LEARN MORE

1.800.662.3537

TOUGHPAD FZ-X1



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

