



GENERAL PURPOSE CORDED HANDHELD LASER BAR CODE READER

With rich feature sets and extensive model options, the Gryphon™ product series from Datalogic ADC represents the premium level of data collection equipment for general purpose applications.

For customers who want the high performance associated with laser scanning technology, the Gryphon GD4300 scanner is an ideal solution providing longer reading distances, snappy performance with a bright, well-defined scan line. Poor quality bar codes and low contrast labels with bad edge definition are not a problem for this Gryphon scanner, plus Datalogic's patented Green Spot provides visual good-read feedback directly on the code, allowing for fast and accurate scanning which is especially useful in noisy environments or in places where "beep-free" reading is desired.

The scanner's stylish enclosure, light weight and compact size make it perfect for use in retail and office applications. Light industrial users will appreciate the scanner's toughness. Its rubber-like overmold cushions the scanner when dropped, protects the scan window and prevents the scanner from slipping off counter surfaces. Featuring an IP52 sealing rating, its strong enclosure guards against dust and liquid spills, and anti-shock mounts provide additional protection for the internal scan engine and optics.

The Gryphon GD4300 readers offer a choice of two sets of multi-interface options: USB, Keyboard Wedge, RS-232 and Wand Emulation, or for use at the point-of-sale (POS), IBM 46XX, USB and RS-232. Both interface sets offer configuration flexibility and are easily adapted for migration or future changes to the host system. Remote Host Download lowers the service costs and improves operations allowing for hassle-free field upgrades while the Datalogic Aladdin™ configuration software provides user-friendly features that simplify the start-up procedure, especially for inexperienced users.

FEATURES

- Aggressive reading performance: over 100 scans/second
- Excellent depth-of-field over 47.0 cm / 19.0 in
- Datalogic Green Spot for good-read feedback
- Remote Host Download lowers service costs and improves operations (GD4310 Model)
- Multi-interface solutions support most popular interfaces including USB, RS-232, Keyboard Wedge, IBM 46XX and Wand Emulation
- 1.8 m / 5.9 ft Drop Resistance
- Water and Particulate Sealing Rating: IP52
- USB Certified Kits Available



DECODING CAPABILITY

| | |
|-------------------|----------------------------------------------------------------------------------------|
| 1D / LINEAR CODES | Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes. |
| POSTAL CODES | China Post |
| STACKED CODES | GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional |

ELECTRICAL

| | |
|---------------|-------------------------------------------------------------------------------------------------------------------|
| CURRENT | Operating (Typical): GD4310: 185 mA @ 5 VDC; GD4330: 260 mA @ 5 VDC +/- 5%; Standby/Idle (Typical): 30 mA @ 5 VDC |
| INPUT VOLTAGE | GD4310: 4.5 - 14.0 VDC; GD4330: 4.75 - 5.25 VDC |

ENVIRONMENTAL

| | |
|--------------------------------|---------------------------------------------------------------------------------------|
| AMBIENT LIGHT | 0 - 100,000 lux |
| DROP RESISTANCE | Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface |
| ESD PROTECTION (AIR DISCHARGE) | 16 kV |
| HUMIDITY (NON-CONDENSING) | 5 - 90% |
| PARTICULATE AND WATER SEALING | IP52 |
| TEMPERATURE | Operating: 0 to 55 °C / 32 to 131 °F Storage/Transport: 20 to 70 °C / -4 to 158 °F |

INTERFACES

| | |
|------------|--------------------------------------------------------------------------------------------------|
| INTERFACES | RS-232 / IBM 46XX / USB Multi-Interface; RS-232 / USB / Keyboard Wedge / Wand Multi-Interface |
|------------|--------------------------------------------------------------------------------------------------|

PHYSICAL CHARACTERISTICS

| | |
|------------------|-------------------------------------------|
| COLORS AVAILABLE | Black; White |
| DIMENSIONS | 18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in |
| WEIGHT | 169.0 g / 6.0 oz |

READING PERFORMANCE

| | |
|--------------------------------|-----------------------------------------------------------------------------------------------|
| LIGHT SOURCE | Illumination: 630 - 680 nm VLD |
| PRINT CONTRAST RATIO (MINIMUM) | 25% |
| READ RATE (MAXIMUM) | 100 reads/sec. |
| READING ANGLE | Pitch: +/- 50°; Roll (Tilt): +/- 35°; Skew (Yaw): +/- 65° |
| READING INDICATORS | Beeper (Adjustable Tone and Volume); Datalogic 'Green Spot' Good Read Feedback; Good Read LED |
| RESOLUTION (MAXIMUM) | 0.102 mm / 4 mils |

READING RANGES

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPICAL DEPTH OF FIELD | Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. 5 mils: 3.6 to 15.8 cm / 1.4 to 6.2 in 7.5 mils: 3.0 to 25.0 cm / 1.2 to 9.9 in 10 mils: 2.8 to 35.0 cm / 1.1 to 13.8 in 13 mils: 2.2 to 47.5 cm / 0.9 to 18.8 in 20 mils: Up to 69.0 cm / 27.2 in |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SAFETY & REGULATORY

| | |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AGENCY APPROVALS | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| ENVIRONMENTAL COMPLIANCE | Complies to China RoHS; Complies to EU RoHS |
| LASER CLASSIFICATION | Caution Laser Radiation - Do not stare into beam; CDRH Class II; IEC 60825-1 Class 2 |

UTILITIES

| | |
|----------------------|--------------------------------------------------------------------------------|
| DATALOGIC ALADDIN™ | Datalogic Aladdin configuration program is available for download at no charge |
| OPOS / JAVAPOS | OPOS Utilities are available for download at no charge |
| REMOTE HOST DOWNLOAD | Lowers service costs and improves operations |

WARRANTY

| | |
|----------|-------------------------|
| WARRANTY | 5-Year Factory Warranty |
|----------|-------------------------|

ACCESSORIES

Mounts/Stands

- HLD-G040-BK Desk/Wall Holder, G040, Black
- HLD-G040-WH Desk/Wall Holder, G040, White
- STD-G040-BK Basic Stand, G040, Dark
- STD-G040-WH Basic Stand, G040, White





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

