

VersaScan™ II

Long Range CCD Barcode Scanner

High Speed, Long Range Performance

ID TECH's second generation long range CCD barcode scanner, the VersaScan II, boasts a scan rate of 450 scans per second, topping its class. With a competitive scanning range of up to 13.8 inches, the VersaScan II allows for excellent reading at an optimal distance.

Auto-Sensing Capabilities

The VersaScan II features an auto-sensing mode, allowing the scanner to operate while resting in its stand. When the scanner detects a barcode is present, it will automatically activate, allowing users the freedom of scanning barcodes without a scanner in their hands. With two hands free to manage other tasks, the VersaScan II provides added productivity.

Readability of Global 1D Symbolologies

In addition to the freedom provided by the superior transmission range, the VersaScan II has the ability to read all global 1D barcode symbolologies as well as PDF417. With such flexibility, ID TECH's VersaScan II is an excellent scanner for multiple applications.

Features and Benefits:

- Ergonomic design for superior handling
- Long range scanning up to 13.8 inches
- Auto-sensing mode
- Rugged design for industrial environment
- Supports most standard 1D barcode symbolologies plus PDF417
- Data editing features
- Configuration cloning capability
- 450 scans per second
- Trouble-free interchangeable communication cable between PS/2, RS232, and USB Keyboard interfaces



IDTECH®
Value through Innovation

VersaScan™ II Specifications IDBB-42XILRB

Electrical

Power Requirements:	5.0 VDC \pm 5%
Interfaces:	PS/2, RS232, USB Keyboard
Light Source:	660 nm visible red LED
Sensor:	2048 pixel CCD

Environmental

Operating Temperature:	0°C to 50°C (32°F to 122°F)
Storage Temperature:	-20°C to 60°C (-4°F to 140°F)
Humidity:	20% - 85% non-condensing
Drop Test:	5.9 feet (1.8 m)

Mechanical

Dimensions:	6.29 inches (160 mm) x 2.72 inches (69 mm) x 3.46 inches (88 mm)
Weight:	4.41 oz. (without cable)
Indicator:	LED, beep tone
Color:	Black
Field Width:	7.87 inches (19.99 cm)
Resolution:	0.1mm
PCS:	60% or more
Scan Rate:	450 scans per second
Range:	1.5 inches (3.81 cm) to 13.8 inches (35.05 cm)
Symbologies:	UPC-A/UPC-E, EAN-8/EAN-13, Industrial 2 of 5, Codabar, Matrix 2 of 5, Code 11, Code 93, Code 32, Code 128, Standard Code 39, Full ASCII Code 39, Interleaved 2 of 5, China Postal Code, MSI Plessey Code, UK Plessey Code, EAN/UCC 128, Telepen Code, IATA Code, RSS Code, PDF417
Approvals:	FCC Class B, CE



IDTECH®

Value through Innovation

Corporate Headquarters:

10721 Walker Street, Cypress, California 90630
www.idtechproducts.com
(714) 761-6368 sales@idtechproducts.com

International Sales Office

Canada & South America:

+450 465 5261 (Canada) robertop@idtechproducts.com

European Sales Offices:

+49(0) 8851 6159900 (Germany)
emea@idtechproducts.com

ISO 9001 Certified



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

