# Backlit Washable Keyboard J84-2120 Series

## Medical and Industrial



Corded, Washable, Backlit Keyboard with Integrated Pointing Device, for Medical and Industrial Applications



# **Key Features**

#### Compact, unique, easy-to-wipe key-top

- No room for bacteria and infection traps
- Easy-to-clean surface
- Integrated Pointing Device

#### **CLEAN key**

- Prevents data from being sent while the keyboard is wiped down, allowing user to clean at any interval with minimal downtime
- User is notified of 'lock down mode' by brightly lit CLEAN KEY

#### Rugged and fully sealed

- Completely sealed rubber top casing-NEMA 4 rating
- Suitable for rinsing with cleaning and disinfection fluids. Impervious to typical hospital cleaning solution
- Pre-tapped mounting holes for easy installation

## Backlit

Selectable Backlit Key field 4-levels of brightness

## **Pointing Device**

 New Low power, sealed, optical pointing device offers high speed motion detection and no moving parts

## **System Requirements**

 USB supported operating system powered by USB port

#### **Technical Data**

#### Interface

**USB 2.0** 

#### **Current:**

- 5 VDC @ 250 mA typical with backlighting at max brightness
- Radiated immunity: 20 volts / Meter

## Cable Length:

- Approx. 1.02 Meters
- 43.4 Inches

#### **Key Layout**

 83 key position US key layout including Windows keys

#### Weight

- 889 g (without packaging)
- 1.96 lbs (without packaging)
- 1 kg (with packaging)
- 2.2 lbs (with packaging)

## **Pointing Device**

- Sealed optical finger navigation
- Capable of high speed motion detection
- Low power architecture

# **Keyswitch Lifetime:**

3 million operations

# **Technology**

- Feedback: Tactile
- Material: industrial silicon rubber



#### **Technical Data**

## Housing:

- High impact PC/ sealed
- NEMA 4 requirements

## **Storage Temperature:**

- -55°C to 70°C
- -55°F to 158°F

#### **Operating Temperature:**

- -40°C to 70°C
- -40°F to 158°F

## **Humidity:**

**100%** 

#### **Dimensions**

Keyboard: 290 x 162 x 48 mm


Keyboard: 11.4" x 6.4" x 1.9" inches

Packaging: 310 x 202 x 53 mm

■ Packaging: 12.2" x 7.95" x 2.08" inches

## Mounting

VESA mount



#### Compliance:

- CE
- FCC Class B
- UL 60950
- NEMA 4

# **Packaging Unit:**

- 20 keyboards per master carton
- 28 master cartons per pallet

## Warranty

1 Year

# Order Description

Order Number	Interface	Color	LED Color
J84-2120LUBUS-2	USB	BLACK	RED

Available in various country versions upon request.

ZF Electronic Systems Pleasant Prairie, LLC 11200 88th Avenue Pleasant Prairie, WI 53158

USA

Phone: 262.942.6500

Internet: www.cherrycorp.com

Sales: 262.942.6562

E-Mail: CEP\_sales@ZF.com

Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

