



POS Keyboards

## K2724 POS Keyboard with MSR

The K2724 POS Keyboard features a **dual track** Magnetic Stripe Reader and built-in bar code scanner port, providing a space-saving, one-piece solution suitable for point of sale, banking and other commerce applications. It provides basic customization through 21 relegendable keys. Rugged construction and a spill resistant design guarantee an extended life cycle.



## KP2724 Programmable POS Keyboard with MSR

The KP2724 is the programmable version of the K2724. Its features allow full customization of the unit. It supports 24 macros of up to 32 characters each. Every key can be remapped to change the keyboard's layout. Additionally, 90 keys can be relabeled to your specific needs. This prevents mistakes, reduces the learning cycle and speeds up operations.



**K2724 Features**

- Compact, space saving design.
- 21 relegendable keys.
- Built-in dual track Magnetic Stripe Reader.
- Integrated bar code decoder accepts wand, laser scanner, CCD, or RS232 input.
- Spill resistant construction.
- Num-Lock, Caps Lock, Scroll Lock, and Good Read LEDs.

**KP2724 Features**

- Compact, space saving design.
- 24 programmable keys, 32 characters per key.
- 90 relegendable keys.
- 101/102 remappable keys.
- Built-in dual track Magnetic Stripe Reader.
- Integrated bar code decoder accepts wand, laser scanner, CCD, or RS232 input.
- Spill resistant construction.
- Num-Lock, Caps Lock, Scroll Lock, Good Read and Prog. Macro LEDs.

| SPECIFICATIONS                    |   |        |
|-----------------------------------|---|--------|
| Mode                              | K2724   | KP2724 |
| Layout                            | 104   | 101    |
| Relegendable keys                 | 21  | 90     |
| Programmable keys                 | Non-programmable                                  | 24     |
| Remappable keys                   | N/A   | 101    |
| Integrated magnetic stripe reader | Track I & II (ISO 7811)                           |        |
| Built-in bar code decoder         | Decoder accepts wand, CCD, laser, or serial input |        |
| Compatibility                     | IBM AT, PS/2                                      |        |
| Total key travel                  | 4.0 ± 0.3 mm                                      |        |
| Key type                          | Membrane switch, 20 million strokes life cycle    |        |
| Electrical                        | 5V DC ± 5% @ 250 mA                               |        |
| Environmental                     | Operating: 32° to 131° F (0° to 55° C)            |        |
|                                   | Storage: -4° to 149° F (-20° to 65° C)            |        |
|                                   | Humidity: 10 to 95% RH (non-condensing)           |        |
| Dimensions                        | 15.8" x 8.3" x 1.7" (400 x 210 x 43 mm)           |        |
| Warranty                          | One year  |        |



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

