

| Specification               | KS-7715   | KS-7717  |
|-----------------------------|---|--|
| Processor                   | Intel Core i3 2.2 GHz / 3 M cache CPU<br>Intel Core i5 2.5 GHz / 3 M cache CPU  |  |
| System Memory               | DDR3 1066 MHz, SO-DIMM socket x 2, max 8 GB, default 4 GB   |  |
| Storage Device              | 2.5" SATA HDD x 2 or SSD Kit (Optional)   |  |
| Power Supply                | 12V DC power adaptor, 120W<br>(Optional 150W when equipping with 2nd 15" LCD LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045, Black Only)   |  |
| Audio                       | 2W speaker x 2, line out  |  |
| OS support                  | Win 7 / Windows XP Pro / POSReady 7 / POSReady 2009   |  |
| Color                       | Black / White   |  |
| <b>Display</b>              |   |  |
| LCD                         | 15" TFT LCD, 1024 x 768 resolution  | 17" TFT LCD, 1280 x 1024 resolution                        |
| Touch Function              | Resistive, 5-wire, USB Interface / IR touch, USB Interface<br>Bezel-free, Resistive touch, USB Interface<br>Bezel-free, PC touch, USB Interface   | Resistive, 5-wire, USB Interface / IR touch, USB Interface |
| Brightness Control          | By push button  |  |
| Tilt Adjustment             | From 15° to 70°   |  |
| <b>Connectivity</b>         |   |  |
| LAN Port                    | 10 / 100 / 1000 Mb  |  |
| Parallel Port               | Optional  |  |
| Serial Port                 | DB9 x 3, RJ-45 x 1 (Optional RJ45 to DB9 cable)<br>with 5V / 12V support on COM1 / COM2 / COM3 / COM4   |  |
| UPS Port                    | Yes, battery (Optional)   |  |
| Standard USB Port           | 7 ( 6 on the I/O plate, 1 on the left side)   |  |
| Proprietary USB Port        | 1 for side mount options  |  |
| Powered USB                 | 1 X 24V via 5.5th gen base (Upgrade to 150W power adaptor when equipped with Powered USB)   |  |
| VGA Port                    | D-SUB 15 pins, with 12V power for Posiflex LCD monitor  |  |
| CR Port                     | 1, control 2 CR   |  |
| <b>Physical Dimension</b>   |   |  |
| Dimension (W x D x H in mm) | 378 x 312 x 340   | 410 x 312 x 385  |
| Weight (N. W. in kg)        | 9.25  | 11.7   |
| <b>Environment</b>          |   |  |
| Operation Condition         | 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)   |  |
| Storage Condition           | (-20°C) - 70°C, 10%RH - 90%RH   |  |
| <b>Options</b>              |   |  |
| SSD                         | 8 GB minimum  |  |
| 2nd HDD                     | 2.5" SATA HDD   |  |
| RAID Function               | Support RAID 1 (Disk mirroring)   |  |
| UPS Battery                 | 2300 mAh/12V  |  |
| WiFi                        | 802.11 b / g / n, USB interface   |  |
| 2nd LCD Display             | 15" LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045, 12" LM-6101B/LM-2312, 10" LM-2310 (Black Only)   |  |
| MSR                         | See security device   |  |
| Security Device (SD)        | SD-460/SD-460Z : 3 tracks MSR (Optional JIS-II) and/or fingerprint sensor (Black / White)<br>SD-660W : 3 tracks MSR (Optional JIS-II) and/or iButton (Black Only)<br>SD-860W : 3 tracks MSR (Optional JIS-II) and/or RFID and/or WiFi (Black / White) |  |
| PD-306 / PD-306U            | 2 x 20 LCD, default 200 mm pole (Black Only)  |  |
| PD-309 / PD-309U            | 2 x 20 LCD, default 200 mm pole (Black Only)  |  |
| PD-310 / PD-310U            | 2 x 20 LCD, rear top mount (Black / White)  |  |
| PD-2602 / PD-2602U          | 2 x 20 VFD, default 200 mm pole (Black Only)  |  |
| PD-2604 / PD-2604U          | 2 x 20 VFD, rear top mount (Black / White)  |  |
| PD-2605 / PD-2605U          | 2 x 20 VFD, default 200 mm pole (Black Only)  |  |
| PD-76X2                     | 240 x 64 dot graphics LCD, 200 mm pole (Black Only)   |  |
| KP-300W                     | 36 Key plus lock keypad and/or MSR and/or smart card reader (Black Only)  |  |
| Certifications              |   |  |

## KS-7700 Series

The World's First Intel Core i5 FanFree POS System  
Elegant Bezel-Free Design



Design and Manufacturing In Taiwan by Posiflex Technology Inc.  
\*\* The product information and specifications are subject to change without prior notice.

2012 KS7704C1

## KS-7700 Series

Posiflex unveils the World's First Intel Core i5 FanFree POS System the KS-7700 series.

The KS-7700 series adopts up to Intel Core i5 CPU, RAID backup, and UPS functions with bezel-free touch screen in its streamlined and patent aluminum die casting enclosure. Accompanying with bezel-free design and slim base stand, the fashionable look conveys a sense of elegance and style. The built-in UPS function is embedded on main board developed by Posiflex for power backup. And the FanFree structure boasts anti-dust and silent operating advantages to meet the requirements of harsh and quiet environments, respectively.

Besides, the KS-7700 series supports versatile accessories and peripherals such as wireless module, MSR, customer pole display, programmable keypad, as well as a wide range of connectivity options to meet numerous applications.

The KS-7700 series aims to fulfill the requirements of high-end segment retails.



### Key Features

- ▶ Equipped with up to Intel Core i5 2.5GHz (Optional) and DDR3 memory
- ▶ Resistive, IR, Bezel-free Resistive, or Bezel-free PC touch screen (Bezel-free option for KS-7715 only)
- ▶ 17" LCD 1280 x 1024 (KS-7717) or 15" LCD 1024 x 768 resolution (KS-7715)
- ▶ RAID 1 (Disk Mirroring) support to backup important data
- ▶ UPS (Embedded on main board developed by Posiflex) support to avoid sudden loss of power during transaction
- ▶ FanFree design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Bottom cable guide design and cover for safety and neat outlook
- ▶ Firm and slim base stand
- ▶ Shiny diamond black or white front bezel for stunning look (Optional)





[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

